



LIGHT now



Light up Your world. Now


#ImprovingLives

bticino

A brand of  legrand®



LIGHT *now*





Light up Your world. Now

Merging timeless minimalist design with cutting-edge smart technologies, Light Now redefines your home management experience. Compatible with both traditional installation systems and the latest smart home solutions, Light Now is also an eco-friendly range that prioritizes sustainability by minimizing energy use and utilizing green materials, to reduce the ecological footprint.

Step into the next era of the smart home - light up your world, reduce impact, live smarter. Now.

LIGHTnow

LIGHTnow



Light up Your world. Now

Summary

Design and Green Vision

Design	4
Colors: a careful selection	6
Materials	14
Responsible packaging	17
Green Vision	18

Technology for the Smart Home

Appropriate technology for your electrical system	20
Light Now with Netatmo	26
Light Now MyHOME	30
Light Now KNX	34

A high-quality installation


Lighting frame, floating frame, supporting frame and protection	38
2 and 3 modules standard installation	40
Controls: traditional and touchless	43

Catalogue

Switches, sockets and cover plates for the residential electrical system	45
Smart home - Light Now with Netatmo	70
Smart home - Light Now MyHOME	84
Smart home - Light Now KNX	100
Solutions fo tertiary sector	106
Dimensional data	117

Design

Extreme minimalism. Timeless beauty.




Pure design

A minimal and pure design where every detail becomes the protagonist.

Perfect alignment between cover plates and axial controls. Slightly rounded edges.



Light Now has won this prestigious international award, confirming BTicino's ability to combine technology and design.



Light

The distinctive element

Central LED

A discreet central LED, illuminated in white or blue, at the end of the soft signature, makes the control more ergonomic, facilitating its identification.

Lighting frame

A supporting led, optional, and installable even at a later time, allows for elegant illumination at the bottom of the cover plate.

Matter

Tactile sensations



A touch of style

Light Now enhances the material component with slightly grainy surfaces that create sophisticated textures. This feature offers a unique tactile experience and allows for meticulously detailed material combinations.

The ability to choose between smooth or rough surfaces allows you to select the texture that best suits your decor and personal taste.

Colors

A careful selection





Refined matt


Light Now offers elegant monochromatic or tone-on-tone solutions, providing customers with numerous options to integrate the electrical system into sophisticated and harmonious environments.

Monochromatic elegance

Three colors for the mechanisms-White, Stone and Dark-perfectly complement the plates with the same finish, creating a flawless monochromatic effect.



AXIAL



ROCKER

Axial and rocker controls

Finishings

Light Now enhances the material component with slightly grainy surfaces that create sophisticated textures. This feature offers a unique tactile experience and allows for meticulously detailed material combinations.

Axial control

Allows mechanisms to always be aligned with each other to achieve the maximum elegance.


Rocker control

For those who like traditional controls in line with the standard habits.

Finishing collection

Circular. A story about recycling

WHITE




Light Now's Circular collection represents the conscious transformation of pure, all-natural materials such as viscose and mica.


This innovation aims to reduce the use of virgin materials, fitting harmoniously into circular economy practices.

Available in three color variants: pure white with a matte finish, an ever-popular and modern must-have, and two exclusive eco-friendly finishes derived from viscose from fast fashion and Mica from construction waste, giving the surfaces an elegant texture on a smooth surface.

WHITE FIBER



WHITE MICA






Finishing collection

Stone. Inspired by nature

STONE




It draws inspiration from natural elements such as sand and building materials, appreciated for their texture and granularity. This collection, created on a recycled polymer, is distinguished by a new texture that is stunning both to the touch and to the eye.


Three new finishes adapt to evolving lifestyles and spaces: the monochromatic Stone, a lighter one that recalls the shade of sand, and a darker one that recalls concrete.

The water-based paint is made from organic raw materials obtained by fermenting biomass, and the characteristic textured effect is due to insoluble spheres.

SAND STONE



MOKA STONE





Finishing collection

Patina. Celebrating imperfection

DARK



The Patina collection is distinguished by its consciously "imperfect" appearance, celebrating natural beauty and non-uniformity on a recycled polymer.

This effect, ideal for dark rooms that reflect the latest trends, infuses life and personality into any space, defining a sophisticated style that highlights furniture details.

The finish is achieved by applying a lightly pigmented water-based paint, used in controlled quantities. The end result is both durable and distinctive, adding a unique touch to any space.

DARK GREY



DARK GREEN





Materials

Giving a second life to waste

Circularity of materials is a cornerstone of the ecological transition

Light Now involves reduced use of raw materials and broader reuse, recycling, and regeneration of existing materials, thereby reducing waste and minimizing environmental impact.

White Fiber




Composed of

35% VISCOSA

65% RECYCLED-ABS

Fast fashion generates a large amount of waste, which seeks a new existence.

We combined viscose fibers with recycled ABS, achieving an aesthetically intriguing result.



White Mica




Composed of

37% MICA

63% RECYCLED-ABS

Mica is an interesting mineral of natural origin.

We have added mica powder derived from construction waste to recycled polymers, resulting in better technical characteristics, reduced weight and an interesting visual appeal.



Materials

Giving a second life to waste


Stone



Composed of

RECYCLED ABS
and water-based
paint from biomass

The plate, made from recycled ABS, is painted with water-based paint formulated using organic raw materials and materials obtained from biomass fermentation.



Responsible Packaging

100% recyclable paper
and cardboard packaging



Plastic free packaging

100% recyclable paper and cardboard.
Box closure: use of ecological glues only.

Print


Water-based ink
One color only (black)
Use of a lesser amount of ink

Environmental labelling




Reduction of weight and volume

Reduction of packaging
weight and volume through
the use of solid cardboard
instead of fluted one for box
interiors, along with smaller
packaging sizes.



Flow pack

100% Paper
100% Recyclable paper
FSC MIX Certificate.



Green Vision

Our commitment to the environment

The entire Light Now project, in continuity with BTicino values, is based on a sustainable approach which concerns procedures, technologies, environmental impact of the product, materials and packaging.

50% recycled and certified material

Light Now uses 50% recycled materials for coverplates and supports from mechanical and chemical recycling. All plastic suppliers are certified by third parties (QA-CER certified and Polycert Europe certified), demonstrating a real and concrete commitment.

Plastic free


All Light Now product packaging is entirely plastic-free. Additionally, we have optimized weight and volume to the fullest extent possible, significantly minimizing the carbon footprint.

Embracing a sustainable future

Light Now's dedication to sustainability exemplifies BTicino's commitment to a better future. By harnessing solar energy and optimizing all production cycles and processes, BTicino consistently reduces the weight of all product components without compromising quality. This approach underscores our unwavering commitment to eco-sustainability, as the actions we take today shape the world of tomorrow.




Appropriate technology for your electrical system



Beyond traditional systems

With Light Now, in addition to traditional systems with classic wired devices, you can create Smart Home systems with devices radio connected, with MyHOME BUS technology or BUS with KNX standard. With Light Now you are free to choose the technology for every user need and for every type of building.

Light Now with Netatmo



Connected controls for the smart home, which communicate via radio. Fast&easy setup and use. Perfect for retrofit.



Light Now MyHOME



Connected controls for the home automation, which communicate via SCS BTicino BUS. Perfect for new and big installation. Endless possibilities.

Light Now KNX



Connected controls for the home and building automation, which communicate via KNX standard bus. Perfect for limitless expectations. Open to full integration.

One single App,
many connected advantages






App Home + Control

Manage your home in a simple and intuitive way

Regardless of the technology used to create the Smart Home system, via radio or MyHOME BUS, your Customer will be able to manage all the functions in a simple and intuitive way, both inside and outside the home, using iOS or Android mobile devices and the specific Home + Control app.

What your customer can do:

1. Check the lights, shutters and connected loads dealing with.
2. Manage the temperature in the various rooms of the house based on personalized profiles.
3. Check electricity consumption.
4. Receive notifications about the status of the system and of loads.
5. Avoid disconnection (black-out) of loads in case of excessive absorption.
6. Create and manage custom scenarios as well as enable or disable those pre-set during system installation.



Light management,
roller shutters and scenarios:
everything within reach of your voice
with your favorite voice assistants.




Voice control

Thanks to the integration with voice assistants Amazon, Google and Apple, your Customer will be able to manage the functions of the Smart system by voice and by hand free, regardless of technology used to create the system, via radio or via BUS MyHOME.



If the video door entry system is integrated into the system with the Classe 300EOS with Netatmo internal unit, your customer will also be able to use this device to manage all the functions by voice, thanks to the natively integrated Alexa assistant.

**Alexa,
turn on the
kitchen lights**





Light Now with Netatmo

Smart home controls, connected and communicating via radio

You can create a new Smart system or add Smart features to an existing system by installing a specific gateway and devices connected to your home Wi-Fi network.


This process is simple for installers and convenient for customers, who they can easily extend the points control with wireless devices.



Energy saving functions

VIEWING OF ENERGY CONSUMPTION

Using special meters energy, you can view the consumption with the Home + Control app in real time that they can also be consulted on a basis daily, monthly and yearly.




CONTROL OF TEMPERATURE

Control and manage the temperature of your home in a smart way, wherever you are, thanks to integrated wi-fi connectivity, the Home+ Control App and compatibility with voice assistants. You can choose to use the Smarter thermostat for managing the heating or the Smarter AC for cooling the air conditioning with split and fan coil.



ALARM NOTIFICATIONS AND CONTROL ANTI BLACKOUT


When an interruption or problem occurs in the power supply you will receive a notification on your Smartphone. The system automatically disconnects the less important loads to avoid blackouts in the event of excessive current draw; at the end of the overload state the loads will be reactivated without your intervention.



Light Now with Netatmo - Functions for comfort and safety

LIGHT AND SHUTTERS CONTROL

Management of standard lamps and colored with ON/OFF and dimmer modes for optimal comfort. Management of the UP/DOWN position of the roller shutter with level control capability and quick recall of the preferred position. Lights, shutters and loads connected to the sockets can also be activated at times and days set by the user via the Home + Control app.




ACTIVATION OF SCENARIOS

One touch activation on the control device or using the Home + Control app, of more lights and shutters and ideal temperature for creating personalized comfort situations by the user. You can also use the pre-setted EXIT scenario to turn off all the lights and lower all the shutters when you leave the house.



INTEGRATION WITH NETATMO SAFETY DEVICES

At the electrical system can be integrate security solutions Netatmo, such as cameras, sensors for doors and windows, smoke detectors etc.; functions will be managed from the dedicated Home + Security app.



SYSTEM EXPANSION WITH WIRELESS DEVICES

The number of control points in the system can be increased using wireless devices that can be installed anywhere by the user and repositioned according to any new needs.

Wireless controls are available in two versions:

battery-powered and no battery; the latter they are particularly suitable in environments where you want to minimize maintenance of the electrical system.



WIRELESS DEVICES FOR OUTDOORS

For applications where greater protection is required from water, dust and external agents, wireless controls are available without batteries and with IP55 protection rating. Control points for turning on the lights or opening of the gate can be added outside the house without the need for wiring.



Light Now MyHOME

Smart home controls connected via SCS BTicino BUS

The MyHOME system offers advanced solutions for the design, configuration and management of advanced SmartHome functions. MyHOME is a customisable, flexible and integrable BUS system to meet the needs of comfort, energy saving and safety through local and remote control, applicable in any residential context, even in large environments (*).




FREE TO CHOOSE THE SERVER YOU PREFER

To make the most of all the potential of the MyHOME system, you can choose between 2 servers:

- F460 DIN server in the cabinet more suitable for villas or bigger installations or in combination with HOMETOUCH as internal unit.
- Classe300EOS video internal unit with Alexa Built-In. Choose it for Real Estate projects or apartments where Video Door Entry System is included.

Note (*): up to 525 addresses.



NEW MULTIFUNCTION COMMAND


The control experience is now improved with the management of multiple functions (up to 4 functions on 2 modules) over the same modularity following market trends and the advanced home automation systems.

Functions can be combined in different ways and personalized with new dedicated key covers.




LIGHTING MANAGEMENT

MyHOME is now compatible with Dali2 Protocol for the lighting management of ON/OFF, dimmer, RGB RGBW (colour and tunable white) & fade in-out in order to create the ideal atmosphere for any need.



SCENARIOS MANAGEMENT


Since MyHOME is able to manage large installations, up to 525 addresses, it is possible to manage scenarios (setting with just one touch of the lights, of the shutters and the temperature) up to 150 in the Home +Project app and up to 100 in the Home + Control app.



Light Now MyHOME - Energy saving functions


LOAD CONTROL

Monitor the status of your energy devices and keep them always under control. Receive an alert every time one load is disconnected to avoid the blackout and have the possibility to force it.



VIEWING CONSUMPTION AND PRODUCTION DATA

Monitor and optimize total and instant energy consumption and production directly from the devices in your home and discover the new interactive graphs that show the history of energy data.



ZONE TEMPERATURE CONTROL

By installing multiple temperature probes in the rooms of the house it is possible carry out zone control (max. 99) of the temperature for optimize consumption. The profile of ideal temperature is set and customized by the user through the Home + Control app.





App Home + Project

Design and configure the system easily


Home + Project is a tool dedicated to the installer, which simplifies the design and configuration process of the MyHOME system, regardless of the server used, item F460 or Classe 300EOS with Netatmo. It is available in 2 versions: a web App version for designing in the office via a desktop, accessible via the site <https://homeproject.legrand.com/> and an App version for iOS and Android Smartphones and Tablets suitable for use on site.

Discover its new features


To make the installers' experience even more flexible, discover all the new functions released which simplify configuration, making the app more intuitive and complete:

1. Configuration backup and restore
2. Testing of system functions
3. Export of device addresses
4. System configuration even when the Internet is not available
5. Firmware update of the devices
6. "Identify" test for the recognition of the loads
7. Calibration of the temperature probe
8. Association of several control devices with one actuator
9. Automatic association of controls with actuators
10. Even more stable connection to the system
11. Compatibility with Tablet devices
12. Replacement of a device without reconfiguring the system

All projects
at glance



All devices
in detail



Light Now KNX

Connected controls
for the Home and
Building automation,
which communicate
via KNX standard BUS.

Dress KNX systems with Light Now aesthetics.

The Light Now range of devices is completed with a KNX certified multifunction control device that guarantees interoperability both between the KNX products of the BTicino offer and the products of different manufacturers. It will thus be possible to create advanced solutions for the intelligent management of comfort and energy saving functions in hotels, hospitals, tertiary and residential environments.



MULTIFUNCTION CONTROL

Advanced device to be combined with the relevant key covers equipped with graphics, to manage up to 4 functions different configurable with the ETS software and editable at any time.

BUS



Light Now KNX - Functions


LIGHT CONTROL

Management of standard lamps and colored with ON/OFF mode and dimmer for optimal comfort.



SHUTTERS MANAGEMENT

Control of the position UP/DOWN with memorization of favourite position.



MANAGEMENT OF SCENARIOS


Setting with just one touch of the lights, of the shutters and temperature to create comfort situations or prepare the environment for when it's not busy.



Light Now KNX - Devices

TOUCH SCREEN


Devices available with 4" and 5" screen, equipped with a temperature and proximity sensor for centralized management of all functions via dedicated pages.



CONTROLLER

Multi-purpose devices for management of:

- Lighting with ON/OFF or dimmer mode
- Motorized shutters and doors
- Devices HVAC thermoregulation



PRESENCE SENSORS

Apart from simple ON/OFF and dimming controls, sensors provide access to the advanced automation functions required in any "green" building: stand-by/maintained dimming, programmed lighting maintenance as well as scenario triggering dependent on presence/absence, natural light levels or time.



FULL INTEROPERABILITY WITH ALL THIRD PARTY APPLICATIONS AND SYSTEMS

Beyond providing optimum control of lighting, shutters, temperature and socket outlets, the KNX protocol is interoperable with all applications installed: you are free to complete your project with other products (heating and ventilation, fire alarms, emergency lighting, etc.) or software leveraging the KNX standard, whoever supplies them!



BTicino KNX solutions can therefore be integrated into an active general building management system, making it possible to display consumption or to be alerted when a fault occurs!



Security sistem



HVAC system



Energy management



Blind & shutt



Metering



Remote control



Monitoring system



Fire & smoke detection



White goods




Lighting

A high-quality installation

LIGHTING FRAME

A led can be added to the frame to create an elegant light in the ambient, and to provide discreet guide lighting to improve living in the spaces.





Example of use in the hallway or entrance hall

Cases of use

- **Hallway or Entrance:** installed at skirting board height, it turns on when it's dark (e.g., manually via a switch or automatically using a twilight sensor) to assist the movement of people living there.
- **Internal Staircases:** installed at skirting board height, it automatically turns on via a motion sensor when people pass by, facilitating movement in the dark.
- **Children's Bedroom:** Installed at skirting board height and/or light switch height, it turns on when it's dark (e.g., manually via a switch or automatically using a twilight sensor), providing a "courtesy light" in the room.
- **Terrace:** installed at the switch point for terrace light lights up to highlight the status of the terrace light (on/off)

Lighting frame installation





FLOATING FRAME

It's the flexible frame at the back of cover plate that assures perfect allignement and fitting in any condition.

The floating frame gives the possibility of:

- 1) hiding wall defects;
- 2) hiding any irregularity in flush mounted boxes positioning;
- 3) hiding the external collars of plasterboard boxes.

AUTOMATIC TERMINALS

Fast: just a few seconds required for wiring the device.

Simplicity: no special wiring tools required.

Reliable and Resistant: cable connection strength guaranteed across the time

Flexibility: possibility of using cables of different sections.



BETTER PROTECTION

The support has a protective shell, wich can be used to protect supports and mechanisms from possible damage during decorating activities, for example when painting the walls.





STRONGER SUPPORT

Up to 4 times stronger than the current version, thanks to the new geometry and high performance materials.













A high-quality installation

2 MODULES STANDARD INSTALLATION




INSTALLATION OF 2 MODULES SUPPORTING FRAMES


	71 mm center distance installation	57 mm center distance installation
 Y4702 (fixing with screws)	 To place side by side or more supports	
 Y4702G (fixing with clips)	 To place side by side or more supports	 Before placing the supports on top of each other, detach upper and lower sides as indicated
 Y4702GTR (fixing with clips)	 To place side by side or more supports	
 Y4702B (fixing with screws)	 Y4702BS (fixing with screws)	 Before placing the supports on top of each other, detach upper and lower sides as indicated
		Note: for both Y4702B and Y4702BS

A high-quality installation


3 MODULES STANDARD INSTALLATION




3 modules



4 modules




7 modules



3 modules box



3 modules supporting frame




Mechanisms



3 modules cover plate

Controls: traditional and touchless


A full range of controls from which to choose the most appropriate solution.



← On
← Off

Axial control

Designed for maximum elegance, axial control keeps mechanisms perfectly aligned with cover plates



On
Off

Rocker control

Designed for users who appreciate traditional switches in line with their usual practices.






On - Off:
No touch

Touchless controls

With these new highly responsive controls, you only need to bring your hand close without touching the surface to turn on – off the light, ensuring high hygiene even for switches.

Light Now




Standard system

SECTION 1

Light Now

Switches, sockets and cover plates for the residential electrical system.



Type of system	Catalog section
Light Now standard system (Switches, sockets and cover plates for the residential electrical system)	1
Light Now with Netatmo (Connected controls for the smart home, which communicate via radio)	2 + 1
Light Now MyHOME (Connected controls for the smart home, which communicate via SCS BTicino bus)	3 + 1
Light Now KNX (Connected controls for the smart building, which communicate via KNX standard bus)	4 + 1

Light Now
basic control devices



Axial				Rocker	
Description	Color	1 module	2 modules	1 module	2 modules
		Item	Item	Item	Item
1 way switch 1P 10 AX 250 V~ automatic terminals	□ White	YW4051A	YW4051M2A	YW4001A	YW4001M2A
	■ Stone	YG4051A	YG4051M2A	YG4001A	YG4001M2A
	■ Dark	YD4051A	YD4051M2A	YD4001A	YD4001M2A
	○ Neutral	Y4051A	Y4051M2A	Y4001A	
2 way switch 1P 10 AX 250 V~ automatic terminals	□ White	YW4053A	YW4053M2A	YW4003A	YW4003M2A
	■ Stone	YG4053A	YG4053M2A	YG4003A	YG4003M2A
	■ Dark	YD4053A	YD4053M2A	YD4003A	YD4003M2A
	○ Neutral	Y4053A	Y4053M2A	Y4003A	
4 way switch 1P 10 AX 250 V~ screw & plate terminals	□ White	YW4054	YW4054M2	YW4004	YW4004M2
	■ Stone	YG4054	YG4054M2	YG4004	YG4004M2
	■ Dark	YD4054	YD4054M2	YD4004	YD4004M2
	○ Neutral	Y4054	Y4054M2	Y4004	
		Y4054LW*	Y4054M2LW*		
		Y4054LB**	Y4054M2LB**		
Pushbutton 1P (NO) 10 A 250 V~ automatic terminals	□ White	YW4055A	YW4055M2A	YW4005A	YW4005M2A
	■ Stone	YG4055A	YG4055M2A	YG4005A	YG4005M2A
	■ Dark	YD4055A	YD4055M2A	YD4005A	YD4005M2A
	○ Neutral	Y4055A	Y4055M2A	Y4005A	

* Supplied with WHITE LED with high luminous intensity for backlighting (the LED is not interchangeable)

** Supplied with BLUE LED with high luminous intensity for backlighting (the LED is not interchangeable)

Note: neutral controls are supplied without key covers. They must be finished using the key covers listed in the following pages. The key covers of other controls may be replaced by those listed in the following pages.

LEDs for rocker control


LED Color	230 V ~	12/24 V ~
White	LN4742V230T	LN4742V12T
Blue	LN4742V230B	

LEDs for axial control

LED Color	230 V ~	12/24 V ~
White	LN4743/230T	LN4743/12T
Blue	Y4743V230B	Y4743V12B

Note: blue LED can be used to make traditional devices chromatically uniform to smart devices, which are equipped with a blue LED non-replaceable.

LED INSERTION



Light Now

rocker and axial key covers















Lightable key covers



Description	Color	1 module	2 modules
		Item	Item
Rocker	□ White	YW4915	YW4915M2
	■ Stone	YG4915	YG4915M2
	■ Dark	YD4915	YD4915M2
Axial	□ White	YW4916	YW4916M2
	■ Stone	YG4916	YG4916M2
	■ Dark	YD4916	YD4916M2



Note: these key covers are suitable for installation on neutral control devices (supplied without key cover), or as replacement for the original key covers supplied.








Lightable key cover with symbol





Rocker		1 module	2 modules
Description	Color	Item	Item
Key cover with LAMP symbol 	□ White	YW4915A	YW4915AM2
	■ Stone	YG4915A	YG4915AM2
	■ Dark	YD4915A	YD4915AM2
Key cover with BELL symbol 	□ White	YW4915D	YW4915DM2
	■ Stone	YG4915D	YG4915DM2
	■ Dark	YD4915D	YD4915DM2
Key cover with KEY symbol 	□ White	YW4915F	YW4915FM2
	■ Stone	YG4915F	YG4915FM2
	■ Dark	YD4915F	YD4915FM2
Key cover with FAN symbol 	□ White	YW4915R	YW4915RM2
	■ Stone	YG4915R	YG4915RM2
	■ Dark	YD4915R	YD4915RM2
Key cover with BOYLER symbol 	□ White	YW4915S	YW4915SM2
	■ Stone	YG4915S	YG4915SM2
	■ Dark	YD4915S	YD4915SM2
Key cover with HEATER symbol 	□ White	YW4915P	YW4915PM2
	■ Stone	YG4915P	YG4915PM2
	■ Dark	YD4915P	YD4915PM2
Axial			
Key cover with LAMP symbol 	□ White	YW4916A	YW4916AM2
	■ Stone	YG4916A	YG4916AM2
	■ Dark	YD4916A	YD4916AM2
Key cover with BELL symbol 	□ White	YW4916D	YW4916DM2
	■ Stone	YG4916D	YG4916DM2
	■ Dark	YD4916D	YD4916DM2
Key cover with KEY symbol 	□ White	YW4916F	YW4916FM2
	■ Stone	YG4916F	YG4916FM2
	■ Dark	YD4916F	YD4916FM2
Key cover with FAN symbol 	□ White	YW4916R	YW4916RM2
	■ Stone	YG4916R	YG4916RM2
	■ Dark	YD4916R	YD4916RM2
Key cover with BOYLER symbol 	□ White	YW4916S	YW4916SM2
	■ Stone	YG4916S	YG4916SM2
	■ Dark	YD4916S	YD4916SM2
Key cover with HEATER symbol 	□ White	YW4916P	YW4916PM2
	■ Stone	YG4916P	YG4916PM2
	■ Dark	YD4916P	YD4916PM2







Item	2P 1 way switches
<input type="checkbox"/> YW4002 <input type="checkbox"/> YG4002 <input type="checkbox"/> YD4002	 2P 16 A 250 V~ - lightable with led lamps LN4742V230T - LN4742V127T - LN4742V12T - 1 module.
<input type="checkbox"/> YW4011 <input type="checkbox"/> YG4011 <input type="checkbox"/> YD4011	 2P 32 A 250 V~ - 2 modules

Item	Switches with key
<input type="checkbox"/> YW4012 <input type="checkbox"/> YG4012 <input type="checkbox"/> YD4012	 1-way switch 2P 10 AX - 250 V~ with key - the key can be taken out even in the off position - the keys are different - 1 module
<input type="checkbox"/> YW4022 <input type="checkbox"/> YG4022 <input type="checkbox"/> YD4022	 2-way switch 10 AX - 250 V~ with key - the key can be taken out even in the off position - the keys are different - 1 module

Item	Pushbuttons
<input type="checkbox"/> YW4040	 1P (NO) 3A 250 V~ backlighting nameplate (the LED is not interchangeable) with integrated LED 250 V~ 0,5 W white - 2 modules
<input type="checkbox"/> YW4034A <input type="checkbox"/> YG4034A <input type="checkbox"/> YD4034A	 10 A 250 V~ opening pushbutton 1P NO/NC, lightable - automatic terminals - 1 module
<input type="checkbox"/> YW4033 <input type="checkbox"/> YG4033 <input type="checkbox"/> YD4033	 Cord pushbutton 1P NO/NC 10 A 250 V~ - cord length 1,8 m - 1 module
<input type="checkbox"/> YW4055AM2A	 Axial Pushbutton 1P (NO) 10 A 250 VA - Key cover with LAMP symbol - automatic terminals - 2 modules
<input type="checkbox"/> YW4055DM2A	 Axial Pushbutton 1P (NO) 10 A 250 VA - Key cover with BELL symbol - automatic terminals - 2 modules
<input type="checkbox"/> YW4005AM2A	 Rocker Pushbutton 1P (NO) 10 A 250 VA - Key cover with LAMP symbol - automatic terminals - 2 modules
<input type="checkbox"/> YW4005DM2A	 Rocker Pushbutton 1P (NO) 10 a 250 VA - Key cover with BELL symbol - automatic terminals - 2 modules

Item	Key card switches
<input type="checkbox"/> YW4549M2 <input type="checkbox"/> YG4549M2 <input type="checkbox"/> YD4549M2	 Badge-holder pocket for the power supply inside the hotel room - slot light with built-in lamp - 30 second switch-off delay - max. load 30 VA Power supply 230 V~ - 2 modules
<input type="checkbox"/> YW4549 <input type="checkbox"/> YG4549 <input type="checkbox"/> YD4549	 Badge-holder pocket for the power supply inside the hotel room - slot light with built-in lamp - 30 second switch-off delay - max. load 30 VA Power supply 230 V~ - 3 modules
<input type="checkbox"/> YW4548M2 <input type="checkbox"/> YG4548M2 <input type="checkbox"/> YD4548M2	 Badge-holder pocket for the power supply inside the hotel room with RFID technology recognition - slot light with built-in lamp - 30 second switch-off delay - power supply 230 V~ - 2 modules
<input type="checkbox"/> YW4548 <input type="checkbox"/> YG4548 <input type="checkbox"/> YD4548	 Badge-holder pocket for the power supply inside the hotel room with RFID technology recognition - slot light with built-in lamp - 30 second switch-off delay - power supply 230 V~ - 3 modules

Item	Hotel do not disturb / make up the room controls
<input type="checkbox"/> YW4027HN <input type="checkbox"/> YG4027HN <input type="checkbox"/> YD4027HN <input type="checkbox"/> Y4373	 Changeover switch 1P 10 AX 250 V~ for hotel room "do not disturb / make up the room" - not lightable - 1 module  Flush light indicator unit signalling "do not disturb / make up the room", to be used with changeover switch for hotel room - power supply 127/230 V~ - 1 module


Item	Touchless switches
<input type="checkbox"/> YW4003TL <input type="checkbox"/> YG4003TL <input type="checkbox"/> YD4003TL	 Touchless switch for lighting. Allows to control light sources by simply passing the hand in front of the switch. Detection distance 6 cm LED indicator light, activated by default (can be switched off). Mechanism depth 20 mm, compatible with all types of flush-mounting boxes. 2 possibilities of cabling : • With neutral, 3 wires Accepted power by lamp type: - LEDs and CFL lamps: 200 W LED - Incandescent and halogen lamps: 200 W - LEDs, CFLs, halogen lamps, fluorescent tubes with ferromagnetic or electronic transformer: 200 VA • Without neutral, 2 wires Accepted power by lamp type: - LEDs and CFL lamps: 5 to 200 W LED - Incandescent and halogen lamps: 5 to 200 W - LEDs, CFLs, halogen lamps, fluorescent tubes with ferromagnetic or electronic transformer: 5 to 200 VA • 4 modes available: - 1-way switch mode: wiring with or without neutral - 2-way switch mode: wiring with neutral mandatory - Master/Slave mode: wiring with neutral mandatory, 3 slaves max. - Push-button mode: wiring with neutral mandatory, for controlling relays or a "with Netatmo" micromodule - 2 modules
<input type="checkbox"/> YW4005TL <input type="checkbox"/> YG4005TL <input type="checkbox"/> YD4005TL	 Touchless switch for doors, electric and electromagnetic door locks. Allows to control door opening by simply passing the hand in front of the switch. Detection distance adjustable from 10 cm (default setting) to 30 cm LED indicator light, activated by default (can be switched off). Mechanism depth 25 mm, compatible with all types of flush-mounting boxes. Power supply 12 - 24 - 48 V= Available modes : - ON/OFF mode/pulse mode (by default mode) - NC/NO mode (by default mode) - 2 modules.

Light Now


other control devices

Options for the installation of touchless switches for lighting Item YW/YG/YD4003TL


Wiring without neutral




Wiring Line + Neutral




Wiring in NO mode



Wiring in master/slave mode




Wiring with micromodule



Installation of touchless switches for doors Item YW/YG/YD4005TL

Wiring diagram





Light Now




control for shutters and fans




Item
<input type="checkbox"/> YW4027N
<input checked="" type="checkbox"/> YG4027N
<input checked="" type="checkbox"/> YD4027N
<input type="checkbox"/> YW4027NM2
<input checked="" type="checkbox"/> YG4027NM2
<input checked="" type="checkbox"/> YD4027NM2

- Changeover switch**
-  Changeover switch 1P 10 AX - 250 V~
1-0-2 - not lightable - 1 module
-  Changeover switch 1P 10 AX - 250 V~
1-0-2 - not lightable - 2 modules

<input type="checkbox"/> YW4037N
<input checked="" type="checkbox"/> YG4037N
<input checked="" type="checkbox"/> YD4037N
<input type="checkbox"/> YW4037NM2
<input checked="" type="checkbox"/> YG4037NM2
<input checked="" type="checkbox"/> YD4037NM2
<input type="checkbox"/> YW4036
<input checked="" type="checkbox"/> YG4036
<input checked="" type="checkbox"/> YD4036

- Double pushbuttons**
-  Double pushbutton with interlock with UP
and DOWN symbol 1P NO + 1P NO 10 A
250 V~ - not lightable
- 1 module
-  Double pushbutton with interlock with UP
and DOWN symbol 1P NO + 1P NO 10 A
250 V~ - not lightable
- 2 modules
-  Double pushbutton 1P NO + 1P NO 10 A
250 V~ - not lightable - 1 module

Item
<input type="checkbox"/> YW4017
<input checked="" type="checkbox"/> YG4017
<input checked="" type="checkbox"/> YD4017

- Fan controller**
-  Fan controller 4 positions 0-1-2-3
- 2 module

Light Now

dimmers



Item	Dimmers	Item	Dimmers
<input type="checkbox"/> YW4418 <input checked="" type="checkbox"/> YG4418 <input checked="" type="checkbox"/> YD4418	<p>Universal Pushbutton Dimmer - with neutral, 3 wires. Can be associated with one or several push-buttons (non illuminated type). Each push-button able to perform the On/Off and dimming function. Memory level function: Lights come on again at the same lighting level as before they were last switch-off. Lower and upper thresholds setting. Indicator/locator function. For all types of lamps :</p> <ul style="list-style-type: none"> - Dimmable LEDs and CFLs : 0 to 150 W (15 lamps max.) - Halogen, incandescent 230 V~ : 0 to 150 W - Halogen with ferromagnetic or electronic transformer : 0 to 150 VA. <p>Depth 35 mm (with neutral). Standby consumption < 5 mW.</p>	<input type="checkbox"/> YW4410 <input checked="" type="checkbox"/> YG4410 <input checked="" type="checkbox"/> YD4410	<p>Pushbutton dimmer output 0 - 10 V for ballast</p> <ul style="list-style-type: none"> - 100 ÷ 240 V~ 50 ÷ 60 Hz - 2 modules
<input type="checkbox"/> YW4418M2 <input checked="" type="checkbox"/> YG4418M2 <input checked="" type="checkbox"/> YD4418M2	<p>As above</p> <ul style="list-style-type: none"> - 2 modules 	<input type="checkbox"/> YW4417 <input checked="" type="checkbox"/> YG4417 <input checked="" type="checkbox"/> YD4417	<p>Dimmer for (LEDs) DALI ballasts and drivers. For controlling max. 21 RGB (Red/Green/Blue) luminaires</p> <ul style="list-style-type: none"> - 2 modules
<input type="checkbox"/> YW4419M2 <input checked="" type="checkbox"/> YG4419M2 <input checked="" type="checkbox"/> YD4419M2	<p>As above - 2 wires</p> <ul style="list-style-type: none"> - 2 modules 		

	Type	Ergonomic	Item	Current range	Incandescent and halogen	Halogen with electronic transformer	Compact fluorescent	Led lamp	Led DALI ballast	Fluorescent with 0-10 V ballast
	Universal push neutral 1 mod.	Push	YW4418 YG4418 YD4418	240 V 100 V	150 W 75 W	150 W 75 W	150 W 75 W	150 W 75 W		
	Universal push neutral 2 mod.	Push	YW4418M2 YG4418M2 YD4418M2	240 V 100 V	150 W 75 W	150 W 75 W	150 W 75 W	150 W 75 W		
	Universal push without neutral 2 mod.	Push	YW4419M2 YG4419M2 YD4419M2	240 V 100 V	125 V 75 V	125 V 75 V	125 V 75 V	125 V 75 V		
	Ballast 2 mod.	Push	YW4410 YG4410 YD4410	240 V 100 V						600 W 300 W
	DALI 2 mod.	Push	YW4417 YG4417 YD4417	240 V 100 V					OK	

Light Now

thermostats and IR Switches



YD4441



YW4430N



YG4430N



YD4430N



YW4432N



YG4432N



YD4432N

Item
<input type="checkbox"/> YW4441
<input checked="" type="checkbox"/> YG4441
<input checked="" type="checkbox"/> YD4441

Thermostat



Electronic room thermostat – relay output with 1 contact in switching: 8 A - 250 V~ $\mu \cos \phi = 1 / 2$ A - 250 V~ $\mu \cos \phi = 0,6$ - Frequency: 50/60 Hz - 230 V~ power supply - 2 modules

Item
<input type="checkbox"/> YW4431
<input checked="" type="checkbox"/> YG4431
<input checked="" type="checkbox"/> YD4431

<input type="checkbox"/> YW4432N
<input checked="" type="checkbox"/> YG4432N
<input checked="" type="checkbox"/> YD4432N

<input type="checkbox"/> YW4432SN
<input checked="" type="checkbox"/> YG4432SN
<input checked="" type="checkbox"/> YD4432SN

<input type="checkbox"/> YW4430N
<input checked="" type="checkbox"/> YG4430N
<input checked="" type="checkbox"/> YD4430N

IR switches



Switch with passive infrared ray movement sensor, suitable for all types of load including LED lamps - 3 wires – variable-threshold twilight circuit with possibility of exclusion – timing circuit to delay switching off adjustable from 30 seconds to 10 minutes - 230 V~ power supply - 1 module



Switch with passive infrared ray movement sensor, suitable for all types of load including LED lamps - 2 wires – variable-threshold twilight circuit with possibility of exclusion – timing circuit to delay switching off adjustable from 5 seconds to 10 minutes - 230 V~ power supply - Standby consumption < 0,01W. Detection field 170°.

Detection range 8m. Light level threshold setting from 5 to 1275 lux. 4 levels of sensitivity setting.

Accepted power by lamp type :

- LEDs, CFLs : 2 to 100W LED
- Halogens, incandescent : 2 to 150W
- LEDs, CFLs, Halogen, fluo tube with ferromagnetic or electronic transformer: 2 to 150VA. If several sensors are installed on the same circuit, the minimum load changes: refer to the technical sheet. Possibility to install up to 3 sensors in parallel. - 2 modules.



Switch with passive infrared ray movement sensor, suitable for all types of load including LED lamps - 2 wires – variable-threshold twilight circuit with possibility of exclusion – timing circuit to delay switching off adjustable from 5 seconds to 10 minutes - 230 V~ power supply - Standby consumption < 0,01W. Provided with a selector switch to change the operating mode (ON-AUTO-OFF) Detection field 170°

Detection range 8m. Light level threshold setting from 5 to 1275 lux. 4 levels of sensitivity setting.

Accepted power by lamp type :

- LEDs, CFLs : 2 to 100W LED
- Halogens, incandescent : 2 to 150W
- LEDs, CFLs, Halogen, fluo tube with ferromagnetic or electronic transformer: 2 to 150VA. If several sensors are installed on the same circuit, the minimum load changes: refer to the technical sheet. Possibility to install up to 3 sensors in parallel. - 2 modules.



Switch with passive infrared ray movement sensor, suitable for all types of load including LED lamps - 3 wires – variable-threshold twilight circuit with possibility of exclusion – timing circuit to delay switching off adjustable from 5 seconds to 10 minutes - 230 V~ power supply - Standby consumption < 0,015W. Master/Slave function available (10 slaves max. for 1 master) Detection field 170°.

Detection range 8m. Light level threshold setting from 5 to 1275 lux. 4 levels of sensitivity setting.

Accepted power by lamp type :

- LEDs, CFLs : 0 to 500W LED
- Halogens, incandescent : 0 to 2000W
- LEDs, CFLs, Halogen, fluo tube with ferromagnetic or electronic transformer: 0 to 1000VA. - 2 modules

Light Now

socket outlets



YW4141



YG4141



YD4141




Y4141R



YW4142AF



YD4142AF



YG4142M2AF

Item	
<input type="checkbox"/> YW4141	2P+E 16 A 250 V~ socket with earth side contacts - shielded tulip contacts - with screw terminals - 2 modules
<input checked="" type="checkbox"/> YG4141	
<input checked="" type="checkbox"/> YD4141	
<input checked="" type="checkbox"/> Y4141R	
	As above - red color
<input checked="" type="checkbox"/> Y4141G	As above - green color
<input type="checkbox"/> YW4141G	2P+E 16 A 250 V~ socket with earth side contacts - shielded tulip contacts - with screw terminals - 2 modules - for Greece
<input checked="" type="checkbox"/> YG4141G	
<input checked="" type="checkbox"/> YD4141G	
<input checked="" type="checkbox"/> Y4141GR	
	As above - red color
<input checked="" type="checkbox"/> Y4141GG	As above - green color
<input type="checkbox"/> YW4141P	2P+E 16 A 250 V~ socket with earth side contacts - shielded tulip contacts - with screw terminals - with flap - 2 modules
<input checked="" type="checkbox"/> YG4141P	
<input checked="" type="checkbox"/> YD4141P	
<input type="checkbox"/> YW4141PG	2P+E 16 A 250 V~ socket with earth side contacts - shielded tulip contacts - with screw terminals - with flap - 2 modules - for Greece
<input checked="" type="checkbox"/> YG4141PG	
<input checked="" type="checkbox"/> YD4141PG	

Item	
<input type="checkbox"/> YW4142AF	When the plug is inserted the socket surface slides inside the casing; it returns to its initial position when the plug is taken out. 2 P+E 16 A 250 V~ socket - automatic clamps - shielded tulip - 2 module
<input checked="" type="checkbox"/> YG4142AF	
<input checked="" type="checkbox"/> YD4142AF	
<input checked="" type="checkbox"/> Y4142AFR	As above - red color
<input type="checkbox"/> YW4142AFP	When the plug is inserted the socket surface slides inside the casing; it returns to its initial position when the plug is taken out. 2P+E 16 A 250 V~ socket - shielded tulip contacts - with flap - automatic clamps - 2 modules
<input checked="" type="checkbox"/> YG4142AFP	
<input checked="" type="checkbox"/> YD4142AFP	
<input type="checkbox"/> YW4142M2AF	When the plug is inserted the socket surface slides inside the casing; it returns to its initial position when the plug is taken out. 2 x 2P+E 16 A 250 V~ socket - shielded tulip contacts - automatic clamps - duplex 4 modules
<input checked="" type="checkbox"/> YG4142M2AF	
<input checked="" type="checkbox"/> YD4142M2AF	
<input type="checkbox"/> YW4142M3AF	When the plug is inserted the socket surface slides inside the casing; it returns to its initial position when the plug is taken out. 3 x 2P+E 16 A 250 V~ socket - shielded tulip contacts - automatic clamps - triplex 6 modules
<input checked="" type="checkbox"/> YG4142M3AF	
<input checked="" type="checkbox"/> YD4142M3AF	

Item	
<input type="checkbox"/> Y4142AF	2P+E 16 A 250 V~ socket - shielded tulip contacts - automatic clamps - neutral finish to be completed with front cover YW4942AF, YG4942AF, YD4942AF - 2 modules
<input type="checkbox"/> Y4142M2AF	
<input type="checkbox"/> Y4142M3AF	
<input type="checkbox"/> Y4142M2AF	As above - 2 x 2P+E 16 A 250 V~ socket - neutral finish to be completed with front cover YW4942AF, YG4942AF, YD4942AF - duplex 4 modules
<input type="checkbox"/> Y4142M3AF	As above - 3 x 2P+E 16 A 250 V~ socket - neutral finish to be completed with front cover YW4942AF, YG4942AF, YD4942AF - triplex 6 modules

Item	
<input type="checkbox"/> YW4942AF	Cover for items Y4142AF, Y4142M2AF and Y4142M3AF - Flat
<input checked="" type="checkbox"/> YG4942AF	
<input checked="" type="checkbox"/> YD4942AF	


Light Now


socket outlets





Item
<input type="checkbox"/> YW4113
<input checked="" type="checkbox"/> YG4113
<input checked="" type="checkbox"/> YD4113
<input checked="" type="checkbox"/> Y4113R
<input type="checkbox"/> Y4113G
<input type="checkbox"/> Y4113O

Italian Standard P11 socket outlets

- 

2P+E 10 A 250 V~ socket - centre distance 19 mm - shielded tulip contacts Ø 4 mm - 1 module
- 


As above - red color
- 


As above - green color
- 


As above - orange color


<input type="checkbox"/> YW4180
<input checked="" type="checkbox"/> YG4180
<input checked="" type="checkbox"/> YD4180
<input checked="" type="checkbox"/> Y4180R
<input type="checkbox"/> Y4180G
<input type="checkbox"/> Y4180O

Italian Standard P17/11 socket outlets

- 

2P+E 16 A 250 V~ socket - centre distance 19 mm and 26 mm - shielded tulip contacts - for plugs 2 P and 2 P+E 10 and 16 A Italian standard - 1 module
- 


As above - red color
- 


As above - green color
- 


As above - orange color


Item
<input type="checkbox"/> YW4140A16F
<input checked="" type="checkbox"/> YG4140A16F
<input checked="" type="checkbox"/> YD4140A16F
<input type="checkbox"/> Y4140A16FR
<input type="checkbox"/> Y4140A16FG
<input type="checkbox"/> Y4140A16FO

Italian Standard P40 socket outlets - flat

- 

When the plug is inserted the socket surface slides inside the casing; it returns to its initial position when the plug is taken out. Socket 2 P+E 16 A 250 V~ - 19 and 26 mm centre distance in 2-centre configuration - protected tulip contacts; side earth contact for German standard plugs; suitable for: Italian standard plugs 2P and 2 P+E 10/16 A, and 16A, German standard plugs 2P+E 16 A. - 2 modules
- 

As above - red color
- 

As above - green color
- 

As above - orange color

Light Now

socket outlets



YW4150



YG4150



YD4150



YW4164T13



YG4164T13



YD4164T13



YD44126









Item	British standard
<input type="checkbox"/> YW4150 <input checked="" type="checkbox"/> YG4150 <input checked="" type="checkbox"/> YD4150	2 P+E 13 A 250 V~ - 2 modules
Item	Swiss standard
<input type="checkbox"/> YW4164T13 <input checked="" type="checkbox"/> YG4164T13 <input checked="" type="checkbox"/> YD4164T13	2 P+E 10 A 250 V~ socket - 2 modules
<input type="checkbox"/> YW4164T23 <input checked="" type="checkbox"/> YG4164T23 <input checked="" type="checkbox"/> YD4164T23	2 P+E 16 A 250 V~ socket - 2 modules
Item	Israeli standard
<input type="checkbox"/> YW4183 <input checked="" type="checkbox"/> YG4183 <input checked="" type="checkbox"/> YD4183	2 P+E 10/16 A 250 V~ socket - 2 modules





Item	European/american standard
<input type="checkbox"/> YW4126 <input checked="" type="checkbox"/> YG4126 <input checked="" type="checkbox"/> YD4126	2 P+E 16 A 127/250 V~ universal duplex socket - Ø 5 mm shielded tulip contacts - 2 modules
<input type="checkbox"/> YW4185 <input checked="" type="checkbox"/> YG4185 <input checked="" type="checkbox"/> YD4185	2 P+E 16 A 127/250 V~ universal duplex socket - shielded tulip contacts - 3 modules
Item	Shaver socket
<input type="checkbox"/> YW4177 <input checked="" type="checkbox"/> YG4177 <input checked="" type="checkbox"/> YD4177	Shaver socket with insulation transformer - input voltage 230 V~ 50/60 Hz - output voltage 115/230 V~ 20 VA. - 3 modules

Light Now

USB chargers and USB chargers with socket outlet

























Item	USB chargers
<input type="checkbox"/> YW4191A <input checked="" type="checkbox"/> YG4191A <input checked="" type="checkbox"/> YD4191A	 Single USB sockets - 1 x Type-A - 5 V= - 3 A - 15 W. For charging of smartphones, tablets and powerbanks. Consumption in passive mode < 0.1 W - compact format for space gain - 1 module
<input type="checkbox"/> YW4192C <input checked="" type="checkbox"/> YG4192C <input checked="" type="checkbox"/> YD4192C	 Single USB sockets - 1 x Type-C 20 W. For fast charging of smartphones, tablets, powerbanks. Fast charge feature: Power Delivery. Consumption in passive mode < 0.05 W - compact format for space gain - 1 module
<input type="checkbox"/> YW4191AA <input checked="" type="checkbox"/> YG4191AA <input checked="" type="checkbox"/> YD4191AA	 Double USB sockets - 2 x Type-A - 5 V= - 3 A - 15 W. For fast charging of smartphones, tablets, powerbanks. For charging up to two portable devices. Consumption in passive mode < 0.05 W - compact format for space gain - 1 module
<input type="checkbox"/> YW4191AC <input checked="" type="checkbox"/> YG4191AC <input checked="" type="checkbox"/> YD4191AC	 Double USB sockets - Type-A + Type-C - 5 V= - 3 A - 15 W. For fast charging of smartphones, tablets, powerbanks. For charging up to two portable devices. Consumption in passive mode < 0.05 W - compact format for space gain - 1 module
<input type="checkbox"/> YW4191CC <input checked="" type="checkbox"/> YG4191CC <input checked="" type="checkbox"/> YD4191CC	 Double USB sockets - 2 x Type-C - 5 V= - 3 A - 15 W. For fast charging of smartphones, tablets, powerbanks. For charging up to two portable devices. Consumption in passive mode < 0.05 W - compact format for space gain - 1 module
<input type="checkbox"/> YW4293CC <input checked="" type="checkbox"/> YG4293CC <input checked="" type="checkbox"/> YD4293CC	 Double USB socket - 2 x Type-C 30W. Fast charging suitable for laptops, tablets smartphones and powerbanks. For charging up to two portable devices. Fast charge feature: Power Delivery. Consumption in passive mode < 0,1 W - 2 modules
<input type="checkbox"/> YW4294C <input checked="" type="checkbox"/> YG4294C <input checked="" type="checkbox"/> YD4294C	 Single USB sockets - 1 x Type-C 45W For fast charging of smartphones, tablets, powerbanks. Fast charge feature: Power Delivery. Consumption in passive mode < 0,1 W - 2 modules
<input type="checkbox"/> YW4395CC <input checked="" type="checkbox"/> YG4395CC <input checked="" type="checkbox"/> YD4395CC	 Double USB sockets - 2 x Type-C 63 W. For fast charging of laptops, smartphones, tables, powerbanks. Fast charge feature: Power Delivery. Consumption in passive mode < 0,1 W Automatic terminals - 3 modules

Item	USB chargers
<input type="checkbox"/> YW4286C2 <input checked="" type="checkbox"/> YG4286C2 <input checked="" type="checkbox"/> YD4286C2	 Double USB sockets - 2 x Type-C - 15 W. For charging of smartphones, tablets, powerbanks. For charging up to two portable devices. - 2 module
<input type="checkbox"/> YW4287C2 <input checked="" type="checkbox"/> YG4287C2 <input checked="" type="checkbox"/> YD4287C2	 Double USB sockets - 2 x Type-A + Type-C - 15 W. For fast charging of smartphones, tablets, powerbanks. For charging up to two portable devices. - 2 module
<input type="checkbox"/> YW4141USB <input checked="" type="checkbox"/> YG4141USB <input checked="" type="checkbox"/> YD4141USB	USB chargers with socket outlet  German standard electric socket with integrated USB charger. Socket 2 P+E 16 A 250 V~ - protected tulip contacts - side earth contact. 5 Vdc type C USB charger for charging electronic devices up to 1,500 mA. Integrated with a 2-module support, it can be installed instead of an existing socket in a 40 mm deep box. Screw fixing and connection using automatic clamps.
<input type="checkbox"/> YW4142USB <input checked="" type="checkbox"/> YG4142USB <input checked="" type="checkbox"/> YD4142USB	 French standard electric socket with integrated USB charger. Socket 2 P+E 16 A 250 V~ - protected tulip contacts - side earth contact. 5 Vdc type C USB charger for charging electronic devices up to 1,500 mA. Integrated with a 2-module support, it can be installed instead of an existing socket in a 40 mm deep box. Screw fixing and connection using automatic clamps.

Light Now

USB chargers selection table

	Single port	Double port			Single port	Double port	Single port	Double port
	Tipo A	Tipo A+A	Tipo A+C	Tipo C+C	Tipo C	Tipo C+C	Tipo C 45 W	Tipo C+C 63 W
								
								
Max Power per 1 device	15 W	15 W			20 W	30 W	45 W	63 W
Power Delivery 3.0	NO	NO			YES	YES	YES	YES
Quick Charge 3.0	NO	NO			YES	YES	YES	YES
Items	<input type="checkbox"/> YW4191A <input type="checkbox"/> YG4191A <input type="checkbox"/> YD4191A	<input type="checkbox"/> YW4191AA <input type="checkbox"/> YG4191AA <input type="checkbox"/> YD4191AA	<input type="checkbox"/> YW4191AC <input type="checkbox"/> YG4191AC <input type="checkbox"/> YD4191AC	<input type="checkbox"/> YW4191CC <input type="checkbox"/> YG4191CC <input type="checkbox"/> YD4191CC	<input type="checkbox"/> YW4192C <input type="checkbox"/> YG4192C <input type="checkbox"/> YD4192C	<input type="checkbox"/> YW4293CC <input type="checkbox"/> YG4293CC <input type="checkbox"/> YD4293CC	<input type="checkbox"/> YW4294C <input type="checkbox"/> YG4294C <input type="checkbox"/> YD4294C	<input type="checkbox"/> YW4395CC <input type="checkbox"/> YG4395CC <input type="checkbox"/> YD4395CC

	Double port		Single port with socket outlet	
	Type C+C	Type A+C	Type C	Type C
				
				
Max Power per 1 device	15 W	15 W	7,5 W	7,5 W
Power Delivery 3.0	NO	NO	NO	NO
Quick Charge 3.0	NO	NO	NO	NO
Items	<input type="checkbox"/> YW4286C2 <input type="checkbox"/> YG4286C2 <input type="checkbox"/> YD4286C2	<input type="checkbox"/> YW4287C2 <input type="checkbox"/> YG4287C2 <input type="checkbox"/> YD4287C2	<input type="checkbox"/> YW4141USB <input type="checkbox"/> YG4141USB <input type="checkbox"/> YD4141USB	<input type="checkbox"/> YW4142USB <input type="checkbox"/> YG4142USB <input type="checkbox"/> YD4142USB



Item	TV socket 1 module
<input type="checkbox"/> YW4202D <input checked="" type="checkbox"/> YG4202D <input checked="" type="checkbox"/> YD4202D	Direct coaxial socket for single-user aerial systems, including central remote powered systems and single-user central satellite systems with current and signal transfer for the selection of the channels - shielded connection clamps with captive screws - Diam. 9.5 mm - male connector - 1 module
<input type="checkbox"/> YW4202P14 <input checked="" type="checkbox"/> YG4202P14 <input checked="" type="checkbox"/> YD4202P14	Passthrough coaxial socket, -14 dB attenuation, for centralised aerial systems, including central remote powered systems and centralised satellite systems with current and signal transfer for the selection of the channels - shielded connection clamps with captive screws - Diam. 9.5 mm - male connector - 1 module
<input type="checkbox"/> YW4202P10 <input checked="" type="checkbox"/> YG4202P10 <input checked="" type="checkbox"/> YD4202P10	Terminal passthrough coaxial socket, 10dB attenuation, for centralised aerial systems, including central remote powered systems and centralised satellite systems with current and signal transfer for the selection of the channels; shielded connection clamps with captive screws - Diam. 9.5 mm - male connector - 75 Ω incorporated impedance final adapter - 1 module
<input type="checkbox"/> YW4202F <input checked="" type="checkbox"/> YG4202F <input checked="" type="checkbox"/> YD4202F	Type F TV coaxial connector - impedance 75 ohm - screw hook - 1 module
<input type="checkbox"/> YW4214D <input checked="" type="checkbox"/> YG4214D <input checked="" type="checkbox"/> YD4214D	Direct demixed coaxial socket for single-user aerial systems, also remote powered and shunting centralised and for singleuser / shunting centralised satellite systems with current and signal transfer for the selection of the channels; Ø 9.5 mm male TV connector - type F SAT connector - 1 module
<input type="radio"/> S2133	Plug Mobile TV plug and jack - Ø 9.5 mm - white - for TV + SAT jacks
<input type="radio"/> 75RTN	End-resistance End-resistance for TV 75 ohm

Item	TV socket 2 modules
<input type="checkbox"/> YW4202M2D <input checked="" type="checkbox"/> YG4202M2D <input checked="" type="checkbox"/> YD4202M2D	Direct coaxial socket for single-user aerial systems, including central remote powered systems and single-user central satellite systems with current and signal transfer for the selection of the channels - shielded connection clamps with captive screws - Diam. 9.5 mm - male connector - 2 module
<input type="checkbox"/> YW4210M2D <input checked="" type="checkbox"/> YG4210M2D <input checked="" type="checkbox"/> YD4210M2D	Star demixed TV-R-SAT sockets for DVB-T, cablecast and satellite installation UHD TV, 4GLTE compatible. For distribution of TV & Radio signals. Recommended coaxial cable: 17 VATC - Meet EN 50083 and EN 50083-2 European directive. TV male connector (Ø 9.5 mm) - R female connector (Ø 9.5 mm) - SAT F type connector - TV: 5 - 68/320 - 862 MHz; R: 87.5 - 240 MHz; - SAT: 950 - 2400 MHz - attenuation 1.5 dB - 2 modules
<input type="checkbox"/> YW4217M2D <input checked="" type="checkbox"/> YG4217M2D <input checked="" type="checkbox"/> YD4217M2D	Star demixed TV-SAT sockets for DVB-T, cablecast and satellite installation UHD TV, 4GLTE compatible. For distribution of TV & Radio signals. Recommended coaxial cable: 17 VATC - Meet EN 50083 and EN 50083-2 European directive. TV male connector (Ø 9.5 mm) - SAT F type connector - TV: 5-68/120-862 MHz; R: 87.5 - 108 MHz; - SAT: 950-2400 MHz - attenuation 1.5 dB - 2 modules
<input type="checkbox"/> YW4217M2P10 <input checked="" type="checkbox"/> YG4217M2P10 <input checked="" type="checkbox"/> YD4217M2P10	Terminal demixed TV-SAT sockets for DVB-T, cablecast and satellite installation UHD TV, 4GLTE compatible. For distribution of TV & Radio signals. Meet EN 50083 and EN 50083-2 European directive - TV male connector (Ø 9.5 mm) - SAT F type connector - TV: 5-68/120-862 MHz; R: 87.5 - 108 MHz; - SAT: 950-2400 MHz - attenuation 10 dB - 2 modules
<input type="checkbox"/> YW4217M2P14 <input checked="" type="checkbox"/> YG4217M2P14 <input checked="" type="checkbox"/> YD4217M2P14	Passthrough demixed TV-SAT sockets for DVB-T, cablecast and satellite installation UHD TV, 4GLTE compatible. For distribution of TV & Radio signals. Meet EN 50083 and EN 50083-2 European directive - TV male connector (Ø 9.5 mm) - SAT F type connector - TV: 5-68/120-862 MHz; R: 87.5 - 108 MHz; - SAT: 950-2400 MHz - attenuation 14 dB - 2 modules
<input type="checkbox"/> YW4207 <input checked="" type="checkbox"/> YG4207 <input checked="" type="checkbox"/> YD4207	cover TV-R-SAT - 2 modules

Light Now

RJ, data, audio and video connectors



Item	RJ11 Connectors				
<input type="checkbox"/> YW4258RJ11 <input type="checkbox"/> YG4258RJ11 <input type="checkbox"/> YD4258RJ11		Tipo of connector RJ11	N° Of pair 2	For plug item 2841/2	Type of connection K10
<input type="checkbox"/> YW4238 <input type="checkbox"/> YG4238 <input type="checkbox"/> YD4238		telephone socket - Israeli standard without shutter - 1 module			

Item	RJ45 connectors				
<input type="checkbox"/> YW4279C5E <input type="checkbox"/> YG4279C5E <input type="checkbox"/> YD4279C5E		Tipo of connector RJ45	N° Of pair 5E	For plug item UTP	Type of connection Toolless IDC
<input type="checkbox"/> YW4279C6 <input type="checkbox"/> YG4279C6 <input type="checkbox"/> YD4279C6		RJ45	6	UTP	Toolless IDC
<input type="checkbox"/> YW4279C6A <input type="checkbox"/> YG4279C6A <input type="checkbox"/> YD4279C6A		RJ45	6A	UTP	Toolless IDC
<input type="checkbox"/> YW4279C6S <input type="checkbox"/> YG4279C6S <input type="checkbox"/> YD4279C6S		RJ45	6	STP	Toolless IDC
<input type="checkbox"/> YW4279C6AS <input type="checkbox"/> YG4279C6AS <input type="checkbox"/> YD4279C6AS		RJ45	6A	STP	Toolless IDC

Item	Audio video connectors	
<input type="checkbox"/> YW4269R <input type="checkbox"/> YG4269R <input type="checkbox"/> YD4269R		Double RCA connector - red and yellow collars - pre-connected - 1 module
<input type="checkbox"/> YW4280 <input type="checkbox"/> YG4280 <input type="checkbox"/> YD4280		Connector jack 3.5 - 1 module
<input type="checkbox"/> YW4294 <input type="checkbox"/> YG4294 <input type="checkbox"/> YD4294		Connector for speakers home cinema - 1 module
<input type="checkbox"/> YW4284P <input type="checkbox"/> YG4284P <input type="checkbox"/> YD4284P		Pre-connected HDMI 2.0 connector - 1 module
<input type="checkbox"/> YW4285P <input type="checkbox"/> YG4285P <input type="checkbox"/> YD4285P		Pre-connected type A USB connector - 1 module

Item	Connectors for optical fiber connections	
<input type="checkbox"/> YW4268LC <input type="checkbox"/> YG4268LC <input type="checkbox"/> YD4268LC		Coupling connector for optical fiber - LC cable socket - duplex - 1 module
<input type="checkbox"/> YW4268ST <input type="checkbox"/> YG4268ST <input type="checkbox"/> YD4268ST		Coupling connector for fiber optic cable - ST termination - duplex - 1 module
<input type="checkbox"/> YW4268SC <input type="checkbox"/> YG4268SC <input type="checkbox"/> YD4268SC		Coupling connector for fiber optic cable - SC termination - duplex - 1 module

Light Now

audible and luminous signalling devices - Lighting




Item	Bells
<input type="checkbox"/> YW4351V12 <input type="checkbox"/> YG4351V12 <input type="checkbox"/> YD4351V12 <input type="checkbox"/> YW4351V230 <input type="checkbox"/> YG4351V230 <input type="checkbox"/> YD4351V230	bronze bell 12 V~ - 5 VA - 80 dB - 1 module bronze bell 230 V~ - 8 VA - 80 dB - 1 module
Item	Buzzers
<input type="checkbox"/> YW4356V12 <input type="checkbox"/> YG4356V12 <input type="checkbox"/> YD4356V12 <input type="checkbox"/> YW4356V230 <input type="checkbox"/> YG4356V230 <input type="checkbox"/> YD4356V230	Buzzer 12 V~ - 5VA - 80 dB - 1 module Buzzer 230 V~ - 5VA - 80 dB - 1 module
Item	Flush light indicator unit
<input type="radio"/> Y4370V12 <input type="radio"/> Y4370V230	Power supply 12/24 V~/c.c. - red, green, blue, white colour - 2 modules Power supply 127/230 V~ - red, green, blue, white colour - 2 modules

Item	Lighting
<input type="checkbox"/> YW4362 <input type="checkbox"/> YG4362 <input type="checkbox"/> YD4362	Reading lamp dimmable - installing the head of the bed allowing you to have a directional light. It is equipped with a flexible arm (length 31 cm) that allows you to orient the illuminating ends. The light intensity can be dimmed by pressing and holding the On / Off integrated command. It can also be connected to a remote control and, if necessary, you can disable the built-in command with a 30 sec pressure - LED light - Consumption 3 W - Luminous Flux 110 lumens (equivalent to 15 W incandescent) - Duration 40.000 hours - 1 module (recessed)
<input type="checkbox"/> YW4382 <input type="checkbox"/> YG4382 <input type="checkbox"/> YD4382	Step marker lamps with white light LEDs - 127/230 V~ - on-off switch - 0.15-0.5 W - 2 modules
<input type="checkbox"/> YW4382IR <input type="checkbox"/> YG4382IR <input type="checkbox"/> YD4382IR	Step marker light + IR sensor, with white light LED and ON-OFF switch - 230 V~ 0,5 W - 2 modules
<input type="radio"/> Y4380	Removable and rechargeable torch with automatic switching on device - it lights up automatically when there is a power cut - push&pull pull-out system complete with recharge base- white light LED with high luminous efficiency - ON/ OFF switch and SPOT pushbutton to increase the brightness when necessary - interchangeable Ni-MH batteries without "memory" effect - 2 hour life - low consumption in stand-by 0.4 W - 230 V~ power supply - 2 modules
<input type="radio"/> Y4380NB	Spare battery for removable led lamp
<input type="radio"/> Y4381	LED safety lamp with automatic operation when there is a power cut. 230 V~ 50/60 Hz - power consumption 2.5 VA (0.1 W) - rechargeable non-replaceable NiMH 3.6 V 140 mAh battery - complete charge in 48 hours - life 2 hours - maximum cable section 1 x 1.5 mm ² - light intensity 2400 mcd - angle of emission 120° - not pull-out - 1 module
<input type="radio"/> J4383	Emergency LED light with automatic activation in case of power cut. LED voltage presence signaling. Rechargeable and replaceable Lithium LiFePO4 3,2 V 1,5 Ah battery. Preset autonomy of 1 hour (98 lumen) can be set to 3 hours (70 lumens) via special jumper. Complete charge in 24 hours. Power supply 230 V~, power consumption 1.8 W - monoblock stand alone - 3 modules

Bulkhead light indicator for off-door signalling and lamp holders. One product for four different colours.

Example with lamp holder item Y4370V230 or item Y4370V12




Choose the product according to the operating voltage and set it with the light colour you need.

Wiring diagram

Y4370V230 and Y4387V230

Note: for 12/24 V powered versions use a suitable transformer









Light Now


electrical safety devices and fuse carriers






blank plates



Item	Automatic thermal magnetic circuit breakers				
<input type="checkbox"/> YW4301A10 <input type="checkbox"/> YG4301A10 <input type="checkbox"/> YD4301A10 <input type="checkbox"/> YW4301A16 <input type="checkbox"/> YG4301A16 <input type="checkbox"/> YD4301A16	 	Type Two-pole Two-pole	In 10A 16A	Vn 230 V~ 230 V~	Breaking powers 1500 A 230 V~ 1500 A 230 V~

Automatic earth-leakage circuit breakers					
<input type="checkbox"/> YW4305A10 <input type="checkbox"/> YG4305A10 <input type="checkbox"/> YD4305A10 <input type="checkbox"/> YW4305A16 <input type="checkbox"/> YG4305A16 <input type="checkbox"/> YD4305A16 <input type="checkbox"/> YW4306A10 <input type="checkbox"/> YG4306A10 <input type="checkbox"/> YD4306A10 <input type="checkbox"/> YW4306A16 <input type="checkbox"/> YG4306A16 <input type="checkbox"/> YD4306A16	   	In 10A 16A 10A 16A	Vn 230 V~ 230 V~ 230 V~ 230 V~	Breaking powers 1500 A 230 V~ 1500 A 230 V~ 1500 A 230 V~ 1500 A 230 V~	IΔn 10 mA 10 mA 30 mA 30 mA




















Fuse carrier	
<input type="checkbox"/> YW4321 <input type="checkbox"/> YG4321 <input type="checkbox"/> YD4321	 Fuse-carrier for 5 x 20 and 6.3 x 32 fuse - max. 10 A 250 V~ - 1 module

Item	Blank plates	
<input type="checkbox"/> YW4950 <input type="checkbox"/> YG4950 <input type="checkbox"/> YD4950 <input type="checkbox"/> YW4950M2 <input type="checkbox"/> YG4950M2 <input type="checkbox"/> YD4950M2 <input type="checkbox"/> YW4953 <input type="checkbox"/> YG4953 <input type="checkbox"/> YD4953 <input type="checkbox"/> YW4953M2 <input type="checkbox"/> YG4953M2 <input type="checkbox"/> YD4953M2 <input type="checkbox"/> J4949	    	Blank plate - 1 module Blank plate - 2 modules Simple output ø 9.5 mm - 1 module Simple output ø 9.5 mm - 2 modules Technic blank plate - 1/2 module To be used when installing a 2 module centred cover plates on 3 module supporting frame

Light Now - 3 modules area installation system

cover plates installation

SELECTION TABLE

























Flush-mounting boxes - masonry	 503E (108x74x53.5 mm)	 504E (133x74x53.5 mm)	 506L (183.5x90x53.5 mm)
Flush-mounting boxes - plasterboard	 PB503N (110x71x52 mm)	 PB504N (132.5x71x52 mm)	 PB506N (183x71x52 mm)
Surface mounting boxes	 503BI	 503BP	 504BI
Supporting frames	 Y4719 (screws)	 Y4703 (screws)	 Y4704 (screws)
N° modules	 2 modules (*)	 3 modules	 4 modules
Cover plates	 YA4819..	 YA4803..	 YA4804..
			 YA4807..

(*) The 3-module supporting frame item Y4703 can also be used to mount the 2-module centred cover plate item YA4819.. In this case, for the composition, it is necessary to use two "half module blank plate" item **J4949** mounted on the right and left sides of the supporting frame.

Light Now - 2 modules area installation system (center distance 71 mm)









cover plates installation

SELECTION TABLE

Flush-mounting boxes - masonry	 500 (Ø 60x44 mm)	 502E (70x70x50)	 502E (70x70x50)				
Flush- mounting boxes - plasterboard		 PB502N (Ø 71x50.5 mm)	 PB502N (Ø 71x50.5 mm)				
Surface mounting boxes		 502BI	 502BI				
Supporting frames	 Y4702G (clips)	 Y4719G (clips)	 Y4702GTR (clips)	 Y4702B (screws)	 Y4702BS (screws)	 Y4702 (screws)	 Y4719 (screws)
N° modules 71 mm	 2 modules	 2 modules	 2 + 2 modules	 2 + 2 + 2 modules	 2 + 2 + 2 + 2 modules		
Cover plates 71 mm	 YA4802..	 YA4819..	 YA4802M2..	 YA4802M3..	 YA4802M4..		

Light Now - 2 modules belgian installation system


cover plates installation

Boxes		
Supporting frames	 Y4702B or Y4702BS (fixing with screws)	
N° modules 57 mm	 2 + 2 modules	 2 + 2 + 2 modules
Cover plates 57 mm	 YA4832M2..	 YA4832M3..


Light Now

cover plate finishing 3 modules area


CIRCULAR



WHITE - **WW**




WHITE FIBER - **WV**




WHITE MICA - **WM**


STONE



STONE - **GG**




SAND STONE - **GS**




MOKA STONE - **GM**

PATINA



DARK - **DD**










DARK GREY - **DS**



DARK GREEN - **DG**

3 MODULES AREA INSTALLATION STANDARD

Finish		2 modules	2 centered modules	3 modules	4 modules	7 modules
CIRCULAR						
	WHITE	YA4802WW	YA4819WW	YA4803WW	YA4804WW	YA4807WW
	WHITE FIBER	YA4802WV	YA4819WV	YA4803WV	YA4804WV	YA4807WV
	WHITE MICA	YA4802WM	YA4819WM	YA4803WM	YA4804WM	YA4807WM
STONE						
	STONE	YA4802GG	YA4819GG	YA4803GG	YA4804GG	YA4807GG
	SAND STONE	YA4802GS	YA4819GS	YA4803GS	YA4804GS	YA4807GS
	MOKA STONE	YA4802GM	YA4819GM	YA4803GM	YA4804GM	YA4807GM
PATINA						
	DARK	YA4802DD	YA4819DD	YA4803DD	YA4804DD	YA4807DD
	DARK GREY	YA4802DS	YA4819DS	YA4803DS	YA4804DS	YA4807DS
	DARK GREEN	YA4802DG	YA4819DG	YA4803DG	YA4804DG	YA4807DG


Supporting frames

Screws	Y4702	Y4719 Y4719G	Y4703	Y4704	Y4707
--------	-------	-----------------	-------	-------	-------


Light Now

cover plate finishing 2 modules ares


CIRCULAR



WHITE - **WW**




WHITE FIBER - **WV**




WHITE MICA - **WM**


STONE



STONE - **GG**



SAND STONE - **GS**




MOKA STONE - **GM**


PATINA



DARK - **DD**



DARK GREY - **DS**



DARK GREEN - **DG**

2 MODULES AREA INSTALLATION STANDARD

Finish	2 modules	2+2 modules 71 mm	2+2+2 modules 71 mm	2+2+2+2 modules 71 mm	2+2 modules belgian system	2+2+2 modules belgian system
--------	-----------	----------------------	------------------------	--------------------------	-------------------------------	---------------------------------

CIRCULAR

	WHITE	YA4802WW	YA4802M2WW	YA4802M3WW	YA4802M4WW	YA4832M2WW	YA4832M3WW
	WHITE FIBER	YA4802WV	YA4802M2WV	YA4802M3WV	YA4802M4WV	YA4832M2WV	YA4832M3WV
	WHITE MICA	YA4802WM	YA4802M2WM	YA4802M3WM	YA4802M4WM	YA4832M2WM	YA4832M3WM

STONE

	STONE	YA4802GG	YA4802M2GG	YA4802M3GG	YA4802M4GG	YA4832M2GG	YA4832M3GG
	SAND STONE	YA4802GS	YA4802M2GS	YA4802M3GS	YA4802M4GS	YA4832M2GS	YA4832M3GS
	MOKA STONE	YA4802GM	YA4802M2GM	YA4802M3GM	YA4802M4GM	YA4832M2GM	YA4832M3GM

PATINA


	DARK	YA4802DD	YA4802M2DD	YA4802M3DD	YA4802M4DD	YA4832M2DD	YA4832M3DD
	DARK GREY	YA4802DS	YA4802M2DS	YA4802M3DS	YA4802M4DS	YA4832M2DS	YA4832M3DS
	DARK GREEN	YA4802DG	YA4802M2DG	YA4802M3DG	YA4802M4DG	YA4832M2DG	YA4832M3DG








Supporting frames

Clips	Y4702G Y4702GTR Y4702B	Y4702G (2x) Y4702GTR (2x) Y4702B (2x)	Y4702G (3x) Y4702GTR (3x) Y4702B (3x)	Y4702G (4x) Y4702GTR (4x) Y4702B (4x)	Y4702G (2x) Y4702GTR (2x) Y4702B (2x)	Y4702G (3x) Y4702GTR (3x) Y4702B (3x)
Screws	Y4702 Y4702BS	Y4702 (2x) Y4702BS (2x)	Y4702 (3x) Y4702BS (3x)	Y4702 (4x) Y4702BS (4x)	Y4702BS (2x)	Y4702BS (3x)


Light Now

supporting frames, LED for supporting frames and accessories















Item	Accessories
○ 503CG	 Protective cover for flush-mounting box 503E, to be used during the building work
○ 503EV	 Vertical inner liner in resin for box item 503E
○ 503EC	 Cover for box 503E used as a junction box - frosted surface for painting - concealed screws - white colour
○ 504EC	 Cover as above - for box item 504E
○ 503ED	 Horizontal and vertical coupling for boxes item 503E and 504E
○ 500/00	 Pair of screws long 35 mm for mounting of supports on flush-mounting boxes
○ Y4000	 Screws for supporting frame 2 modules



Lighting frame



Note: the Lighting frame (Items Y4702X, Y4703X) must be powered with 230V~. Like a normal backlight LED, depending on the mode of use, it can also be connected to other control devices (switches, IR sensors, etc.)

Item	Supporting frames
○ Y4702	 Supporting frame 2 modules with protective shell - fixing with screws
○ Y4702G	 Supporting frame 57/71 mm 2 modules
○ Y4702GTR	 Supporting frame 71 mm 2 modules Turkey standard
○ Y4702B	 Supporting frame 57/71 mm 2 modules - for screws (not supplied)
○ Y4702BS	 Supporting frame 57/71 mm 2 modules - supplied with screws item Y4000 - fixing with screws
○ Y4719	 Supporting frame 2 modules centred - fixing with screws
○ Y4719G	 Supporting frame 2 modules centred - fixing with clips
○ Y4703	 Supporting frame 3 modules - fixing with screws
○ Y4704	 Supporting frame 4 modules - fixing with screws
○ Y4707	 Supporting frame 7 modules - fixing with screws

Item	Lighting frames
○ Y4702X	 Lighting frame 2 modules, with transparent plastic base The LED is not interchangeable - 230 V~
○ Y4703X	 Lighting frame 3 modules, with transparent plastic base The LED is not interchangeable - 230 V~

Item	Protective shell
○ Y4782	 protective shell for 2 modules supporting frame Y4702
○ Y4783	 protective shell for 3 modules supporting frame Y4703

Light Now

surface and waterproof installation



28402W



28403W



28402C



28402CP



28403C



28410



28411



28900



28411P16



28411P



28411P25





Item	IP40 boxes
□ 28402W	IP40 box - 2 modules - white
□ 28403W	IP40 box - 3 modules - white
○ 28402C	IP55 cover - 2 modules
○ 28402CP	IP55 cover - 2 modules (the IP protection rate is guarantee when plugs is in and cover is closed).
○ 28403C	IP55 cover - 3 modules

Item	Accessories
○ 28410	Coupler
○ 28900	IP55 wall-mounting junction boxes 125 x 125 x 56 mm
○ 28411	Cable gland
○ 28411P16	Cable gland with conduit clamp 16 mm
○ 28411P	Cable gland with conduit clamp 20 mm
○ 28411P25	Cable gland with conduit clamp 25 mm


Light Now

Surface and waterproof installation



Item	IP55 cover plates
○ 28603YW	 IP55 cover plate - 3 modules - white
○ 28604YW	 IP55 cover plate - 4 modules - white
○ 28603YD	 IP55 cover plate - 3 modules - black
○ 28604YD	 IP55 cover plate - 4 modules - black

How to install the IP55 cover plates



Note: sequence for installation of 3-module version.
For the 4-module version, proceed similarly using IP55 boxes and plates of the specific modularity.

Light Now

Installation solution for the service sector - installation in wall-mounted boxes, on rails and in multibox boxes installation on plasterboard, masonry wall and profiles

Installation in wall-mounted boxes



502BI



503BI



503BP



504BI

Installation on rails

Boxes



510LN

N° of modules



1 module

Cover plates with support




JA4811M1JW
(White)

Item 510LN: box that can be used also for plasterboard and masonry walls


Installation in Multibox boxes



16102
(170x234x70)



J4718






3 x 6 modules



JA4818JW (White)

Light Now with Netatmo



Connected controls for the Smart Home

SECTION 2

Light Now with Netatmo


Connected controls for the smart home, which communicate via radio.

How to choose devices for the composition of the electrical system

SECTION 2



SECTION 1



Type of system	Catalog section
Light Now standard system (Switches, sockets and cover plates for the residential electrical system)	1
Light Now with Netatmo (Connected controls for the smart home, which communicate via radio)	2 + 1
Light Now MyHOME (Connected controls for the smart home, which communicate via SCS BTicino bus)	3 + 1
Light Now KNX (Connected controls for the smart home, which communicate via KNX standard bus)	4 + 1

Connected controls for the Smart Home


Table of choice


Functions	Wired devices (110-230 V~)				
 Internet connection	<div>      </div> <div> Gateway ...4500C ...4510C, ...4501C, ...4502C (*) Gateway FC80GT (*) Works with Apple Home works with Google Home works with alexa Home + Control </div>				
 Light	<div>       </div> <div> Connected 1-way switch ...4001C Connected 2 way switch ...4003C Connected dimmer ...4011C, ..4012CM2 Connected dimmer without neutral ...4013CM2 Connected lighting micromodule 3584C DIN smart relay FC80RC </div>				
 Shutters and electrical doors	<div>     </div> <div> Changeover switch ...4027C Changeover switch 2 modules ...4027CM2N Connected micromodule ...4027C Connected module for garage door and gate 3586C </div>				
 Scenes					
 Energy management and monitoring	<div>        </div> <div> Connected module for socket ...4531C Connected socket ...4141AC ...4142AC Connected PLUG & PLAY socket 4141PC Smart DIN contactor FC80CC Smart control with dry contact FC80AC Connected DIN load management module FC80GCS Smart DIN meter F20T60A - F40T125A (threephase Systems) </div>				
 Thermo	<div>     </div> <div> Boiler Thermostat ...8002 AC System Thermostat ...8003 IR interface for air conditioning unit 3460IR Actuator for fan coil unit 0 489 10 </div>				

Wireless devices (battery powered)	Wireless devices (no-battery)
<div data-bbox="76 714 252 846"></div> <div data-bbox="75 851 177 943">Light control ...4003CW ...4003CWI (1 module)</div> <div data-bbox="306 714 481 846"></div> <div data-bbox="303 851 403 918">Double light control ...4003DCW</div> <div data-bbox="529 678 646 846"></div> <div data-bbox="525 851 654 918">Wireless motion sensor 3585C</div> <div data-bbox="715 689 807 846"></div> <div data-bbox="713 851 900 943">Wireless motion sensor ... 4007CW ... 4007CWI (1 module)</div>	<div data-bbox="952 714 1128 846"></div> <div data-bbox="951 851 1053 918">Light control ...4003CWG</div> <div data-bbox="1144 714 1319 846"></div> <div data-bbox="1139 851 1249 918">Double light control ...4003CWDG</div> <div data-bbox="1335 703 1469 846"></div> <div data-bbox="1327 851 1468 898">IP55 Light switch 28003CWG</div>
<div data-bbox="76 1003 252 1135"></div> <div data-bbox="75 1131 193 1176">Shutter control ...4027CW</div> <div data-bbox="529 972 617 1135"></div> <div data-bbox="525 1131 644 1200">Shutter control ...4027CWI (1 module)</div>	<div data-bbox="952 1003 1128 1135"></div> <div data-bbox="951 1131 1070 1176">Shutter control ...4027CWG</div> <div data-bbox="1144 992 1278 1135"></div> <div data-bbox="1139 1131 1302 1176">IP55 Shutters switch 28027CWG</div>
<div data-bbox="76 1256 252 1388"></div> <div data-bbox="75 1391 202 1503">Home/Away scenario control ...4570CW ...4570CWI (1 module)</div> <div data-bbox="306 1256 481 1388"></div> <div data-bbox="303 1391 434 1503">Wake Up / Sleep scenario control ...4574CW ...4574CWI (1 module)</div> <div data-bbox="529 1256 705 1388"></div> <div data-bbox="525 1391 676 1438">4 scenarios control ...4575CW</div> <div data-bbox="751 1240 847 1388"></div> <div data-bbox="746 1391 877 1438">Scenario remote control 3528C</div>	<div data-bbox="952 1256 1128 1388"></div> <div data-bbox="951 1391 1080 1458">Home/Away scenario control ...4570CWG</div> <div data-bbox="1144 1256 1319 1388"></div> <div data-bbox="1139 1391 1270 1458">Wake Up / Sleep scenario control ...4574CWG</div> <div data-bbox="1335 1256 1511 1388"></div> <div data-bbox="1327 1391 1484 1438">4 scenarios control ...4575CWG</div>
<p>(*) Note: for the use of the connected devices, the gateway must be installed as part of the system. If the gateway is connected to the internet through the Wi-Fi network, it will be possible to manage the system from the home using the specific HOME + CONTROL App and the vocal commands Google, Alexa and Siri.</p> <p>And if the internet does not work? The devices continue to operate with manual control. The Home+Control app cannot be used.</p>	


Light Now with Netatmo

diagram of a typical smart home system







Optional controls for system expansion via radio - wall installation




Wireless Home&Away
scenario control
item ...4570CW




Wireless Wake up &
Sleep scenario control
item ...4574CW



Wireless light control
item ...4003CW



Wireless shutter control
item ...4027CW



Wireless IP55 light switch
item 28003CWG

Light Now with Netatmo

gateway



FC80GT



YD4510C



YG4500C



YW4500C

Item	Gateway
<input type="checkbox"/> YW4500C <input type="checkbox"/> YG4500C <input type="checkbox"/> YD4500C	Gateway for remote home control (lights, sockets and shutters) using a smartphone (HOME + CONTROL APP required) and/or voice controls (voice assistance required). Supplied with wireless master IN&OUT scenario control, required for the association of all connected devices. Power supply 100-240 V~ - 2 modules
<input type="checkbox"/> YW4510C <input type="checkbox"/> YG4510C <input type="checkbox"/> YD4510C	Gateway as above. Supplied with the flushmounted Home/Away wireless master switch 1 module required for the association procedure of all connected devices. Power supply 110-230 V~ - 2 modules
<input type="radio"/> FC80GT	Gateway as above for DIN switchboard. Supplied without wireless In&Out master scenario control item YW/YG/YD4570CW - 2.5 DIN modules

Item	Gateway with socket
<input type="checkbox"/> YW4501C <input type="checkbox"/> YG4501C <input type="checkbox"/> YD4501C	The gateway creates a connected installation in the home. It can be used to control lights, shutters, and electric appliances plugged into connected sockets:- using the smartphone and the Home + Control app- using the voice assistants- from the general control at the home entrance. It integrates a 2P+E 16 A 250 V~ German standard connected socket for the remote control of electric devices and to monitor their consumption (instantaneous, daily, monthly). Compatible with all the electric devices with power up to 16 A 3680W (with overload protection). It can be installed instead of an existing socket in a 40 mm deep box. Screw fixing and connection using automatic clamps. It has a blue LED that lights up when the socket is ON and that can be configured by means of the Home + Control APP. It can be associated to one or more wireless light controls. It is also supplied with wireless master IN&OUT scenario control, required for the association of all connected devices. Power supply 110-230 V~
<input type="checkbox"/> YW4502C <input type="checkbox"/> YG4502C <input type="checkbox"/> YD4502C	Gateway as above. It integrates a 2P+E 16 A 250 V~ French/ belgian standard connected socket.

Note: for the use of the connected devices, the gateway must be installed as part of the system.


If the gateway is connected to the internet through the Wi-Fi network, it will be possible to manage the system from the home using the specific **HOME + CONTROL App and the vocal commands Google, Alexa and Siri.**

And if the internet does not work?

The devices continue to operate with manual control. The Home+Control app cannot be used.







HOME + CONTROL






Light Now with Netatmo


wired devices for light



Item	Connected 1-way switches
<input type="checkbox"/> YW4001C <input checked="" type="checkbox"/> YG4001C <input checked="" type="checkbox"/> YD4001C	 <p>Connected 1-way switch. It controls the lights locally or remotely. It can be installed like a traditional two-way switch and is compatible with all loads with max. power 250 W. It has a blue LED, which can be configured using the Home + Control App for the localisation and load status functions. It can be associated to one or more wireless controls. Caution: neutral connection is necessary. Power supply 110-230 V~ - 1 module</p>
Item	Connected 2-way switches
<input type="checkbox"/> YW4003C <input checked="" type="checkbox"/> YG4003C <input checked="" type="checkbox"/> YD4003C	 <p>Connected 2-ways switch. It allows to control lights locally or remotely. The connected 2-ways switch has the same installation and usability of a traditional 2-ways switch and it is compatible with all loads with max power 250 W. It is equipped with a blue LED light used always on for localization modality or on, when the light is on for the load status modality. It can be associated with "wireless light switches". Caution: Must be connected to the neutral Power supply 110-230 V~ - 1 module</p>
Item	Connected lighting micromodule
<input checked="" type="checkbox"/> 3584C	 <p>Connected lighting micromodule. It allows to control lights locally or remotely. It is compatible with all loads with max power 300 W. It can be connected to one or more traditional push-button or associated with "wireless light switches". It is installed as a traditional relet in the box (behind the button) or in derivation boxes. Caution: Must be connected to the neutral. Power supply 110-230 V~</p>
Item	DIN smart relay for light control
<input checked="" type="checkbox"/> FC80RC	 <p>DIN smart relay for light control with maximum absorption $I_n = 16$ A. Equipped with contacts for control with remote buttons, up to a maximum of 10. The smart relay allows the lights to be controlled locally and remotely through radio commands, wired buttons, smartphone with the "Home + Control" App or via a voice assistant. Dimensions 1 DIN module. Power supply 110-230 V~ 50/60 Hz.</p>


Item	Connected dimmers
<input type="checkbox"/> YW4411C <input checked="" type="checkbox"/> YG4411C <input checked="" type="checkbox"/> YD4411C	 <p>Dimmer/switch. It allows to control lights locally or remotely, with the dimmer functionality that can be activated from the APP Home+Control. It has the same installation and usability of a traditional switch and it is compatible with all loads (LED, halogen) with max power 150 W at 230 V (or 75 W at 110 V). It is equipped with a blue LED light used for localization modality or load status modality, configurable by APP. It can be connected to one or more traditional push-button or associated with "wireless light switches". Caution: Must be connected to the neutral. Power supply 110-230 V~ - 1 module</p>
<input type="checkbox"/> YW4412CM2 <input checked="" type="checkbox"/> YG4412CM2 <input checked="" type="checkbox"/> YD4412CM2	 <p>Dimmer/switch. It allows to control lights locally or remotely, with the dimmer functionality that can be activated from the APP Home+Control. It has the same installation and usability of a traditional switch and it is compatible with all loads (LED, halogen) with max power 150 W at 230 V (or 75 W at 110 V). It is equipped with a blue LED light used for localization modality or load status modality, configurable by APP. It can be connected to one or more traditional push-button or associated with "wireless light switches". Caution: Must be connected to the neutral. Power supply 110-230 V~ - 2 modules.</p>
<input type="checkbox"/> YW4413CM2 <input checked="" type="checkbox"/> YG4413CM2 <input checked="" type="checkbox"/> YD4413CM2	 <p>Dimmer/switch without neutral. It allows to control lights locally or remotely, with the dimmer functionality that can be activated from the APP Home+Control. It has the same installation and usability of a traditional switch and it is compatible with all loads (LED, halogen) with power 5-300 W at 230 V. It is equipped with a blue LED light used for localization modality or load status modality, configurable by APP. It can be connected associated with "wireless light switches". It doesn't require connection to the neutral, it comes with an active compensator. Power supply 110-230 V~ - 2 modules</p>

Three-point lighting control with connected two-way switch, item ...4003C, installed instead of a traditional two-way switch.



☐ White colour ☒ Stone colour ☒ Dark colour ☐ Neutral item

Three-point lighting control with pushbuttons and connected lighting micromodule, item 3584C, installed instead of a traditional relay.



Light Now with Netatmo

wired devices for shutter and garage, door and gate



YD4027C



YW4027CM2N



4027C



3586C

Item
<input type="checkbox"/> YW4027C <input checked="" type="checkbox"/> YG4027C <input checked="" type="checkbox"/> YD4027C
<input type="checkbox"/> YW4027CM2N <input checked="" type="checkbox"/> YG4027CM2N <input checked="" type="checkbox"/> YD4027CM2N
○ 4027C

Connected devices for shutters



Connected shutter control. It controls a shutter locally or remotely. Compatible with all standard shutter motors (with mechanical or electronic limit switch and maximum power 500 VA), controlled by a wired shutter changeover switch (changeover with the same power supply as the motor). Not compatible with radio controlled or pulse controlled shutter motors. It can be associated to one or more wireless controls. Power supply 100-240 V~ - 1 module



Connected shutter control. It controls a shutter locally or remotely. Compatible with all standard shutter motors (with mechanical or electronic limit switch and maximum power 500 VA), controlled by a wired shutter changeover switch (changeover with the same power supply as the motor). Not compatible with radio controlled or pulse controlled shutter motors. It can be associated to one or more wireless controls. Power supply 100-240 V~ - 2 modules




Connected micromodule for shutters. Associated to one or more shutter wireless controls, it controls a shutter locally or remotely. Compatible with all standard shutter motors (with mechanical or electronic limit switch and maximum power 500 VA), controlled by a wired shutter changeover switch (changeover with the same power supply as the motor). Not compatible with radio controlled or pulse controlled shutter motors. It can be installed in the existing shutter box with no need of masonry works. Power supply 110-230 V~

Item
○ 3586C

Connected module for garage, door and gate



Enables open/close control of a garage door or gate, locally, remotely or via voice assistant. Status display (open/closed/half open) in the Home + Control App. Can be steered using a wireless shutter control or can be controlled from the remote control art.3528C. Supplied with 2 wired position sensors and specific fixtures. Can be installed into an IP55 box 80 x 80 mm or larger. Fitted with 2 separable fixing points. CAUTION: to operate optimally, the gate engine must be setup in step-by-step mode. In this mode the engine workd with the following cycle: OPEN-STOP-CLOSE-STOP-OPEN-



For correct operation, connect also the neutral conductor to the connected devices.

Light Now with Netatmo

wireless controls for light and shutter



YW4003CW



YD4003CWDG



28003CWG



28027CWG



3577C










YG4007CW










3585C



YW4027CWI

Item	Wireless light control
<input type="checkbox"/> YW4003CW <input checked="" type="checkbox"/> YG4003CW <input checked="" type="checkbox"/> YD4003CW	 Wireless light control. It provides ON/OFF control of one or more devices connected for light control. Surface installation with repositionable adhesives (supplied as standard), or inside flush mounted boxes. Built-in battery exhausted LED. CR2032 type 3 V power battery with 8 year expected life supplied (as standard) - 2 modules
<input type="checkbox"/> YW4003CWG <input checked="" type="checkbox"/> YG4003CWG <input checked="" type="checkbox"/> YD4003CWG	 As above. No-Battery - 2 modules
<input type="checkbox"/> YW4003CWI <input checked="" type="checkbox"/> YG4003CWI <input checked="" type="checkbox"/> YD4003CWI	 Wireless light control. It allows the ON / OFF control of one or more connected devices for the lighting control. It can be installed in any flush-mounted box without any wiring. The battery can be replaced without removing it from the supporting frame. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 1 module.
<input type="checkbox"/> YW4003DCW <input checked="" type="checkbox"/> YG4003DCW <input checked="" type="checkbox"/> YD4003DCW	 Double wireless light switch. It is equipped with two buttons to control two different connected devices for lights. Each single button can be associated with one or more devices. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules.
<input type="checkbox"/> YW4003CWDG <input checked="" type="checkbox"/> YG4003CWDG <input checked="" type="checkbox"/> YD4003CWDG	 As above. No-Battery Switch - 2 modules
○ 28003CWG	 Wireless IP55 light switch No-Battery
○ 28027CWG	 Wireless IP55 controller for shutters, gates and garage doors. No-Battery






Item	Wireless light control
○ 3585C	 Wireless motion sensor. It controls one or more devices connected for light control. Infrared detection with angle of 140°. Distance of the adjustable sensor from 2 to 8 m. Switch off delay with 1 to 30 min adjustable delay time and 1 to 1000 lux brightness threshold. Test possible with a 5 sec. delay Recommended assembly height: 2.5 m. Optimum distance between 2 detectors: 6 m. For indoor and outdoor use (IP44). Supplied with 2 1.5V AA batteries for power supply.
<input type="checkbox"/> YW4007CW <input checked="" type="checkbox"/> YG4007CW <input checked="" type="checkbox"/> YD4007CW	 Wireless switches for multicolour lighting. Allow to directly control up to 20 Zigbee 3.0 compatible multi-colour lighting (e.g. Ledvance Smart+ Zigbee, Philips Hue...). To be associated with the lighting in the Home + Control App. Allow ON/OFF and dimming control of 3 light moods which have to be preset in the Home +Control App. Supplied with CR2032 3 V long-life battery for power supply. LED function for low battery indication. Not compatible with WiFi lighting. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. - 2 modules
<input type="checkbox"/> YW4007CWI <input checked="" type="checkbox"/> YG4007CWI <input checked="" type="checkbox"/> YD4007CWI	 As above. Flush-mounting version - 1 module
○ 3577C	 Wireless module for mechanical switch. It allows to change a traditional two-way switch or a pushbutton into a wireless control for one connected device for light control (ON/OFF). The small size allows the installation in the flush mounted box. CR2032 type 3V power battery with 8 year expected life supplied (as standard).





Item	Wireless shutters control
<input type="checkbox"/> YW4027CW <input checked="" type="checkbox"/> YG4027CW <input checked="" type="checkbox"/> YD4027CW	 Wireless shutter control. It allows control of one or more shutter controls. Surface installation with repositionable adhesives (supplied as standard), or inside flush mounted boxes. Built-in battery exhausted LED. CR2032 type 3 V power battery with 8 year expected life supplied (as standard) - 2 modules
<input type="checkbox"/> YW4027CWG <input checked="" type="checkbox"/> YG4027CWG <input checked="" type="checkbox"/> YD4027CWG	 As above. No-Battery Switch - 2 modules
<input type="checkbox"/> YW4027CWI <input checked="" type="checkbox"/> YG4027CWI <input checked="" type="checkbox"/> YD4027CWI	 Shutter wireless switch - It allows the control of one or more connected rolling shutter switches. It can be installed in any flush-mounted box without any wiring. The battery can be replaced without removing it from the supporting frame. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 1 module

Light Now with Netatmo

connected devices for energy management



Item	Connected devices for energy management
<input type="checkbox"/> YW4531C <input checked="" type="checkbox"/> YG4531C <input checked="" type="checkbox"/> YD4531C	 Connected module for socket. When connected to a power socket, it allows remote control of electric devices and also to monitor their consumption (instantaneous, daily, monthly). It is also possible to receive notifications of abnormal consumption levels. Compatible with any electric devices with power up to 3680W with absorption 16A (with overload protection). It has a blue LED, which can be configured using the HOME + CONTROL APP for the localisation and load status functions. Power supply 100-230 V~ - 1 module.
○ FC80CC	 Smart DIN contactor suitable for controlling single-phase loads < 20 A. The smart contactor allows you to remotely control (ON / OFF) loads such as water heaters, swimming pool pumps, induction plates and charging sockets for electric vehicles, from smartphones with the Home + Control App or via a voice assistant. Equipped with a meter for the current absorbed by the load. Dimensions 1 DIN module. Power supply 100-240 V~ 50/60 Hz.
○ F20T60A	 Smart DIN meter. It allows to measure the electrical energy consumption of the entire single-phase system of the house (instantaneous, daily, monthly) and of the single electrical power lines. It allows the reception of notifications in case of reaching the maximum power foreseen by the contract to avoid annoying black-outs. A toroid is supplied to measure the input current. Power supply 100-240 V~ 1 DIN module. (Only for single-phase systems).
○ F40T125A	 Smart DIN meter as F20T60A but for three-phase systems.
○ FC80GCS	 Connected DIN load management module for the monitoring of the consumptions of the whole electric system, the powering or disconnection of the loads, and the setting of scenarios with priority or non-priority loads. When the maximum intended power is reached, the non-priority loads are temporarily disconnected to avoid black-outs. A toroid for the current reading is provided Power supply 110-230 V~ - 1 DIN module

Item	Connected devices for energy management
○ FC80AC	 Smart device for controlling and measuring the consumption of equipment fitted with dry contacts. Rating 12V/30 Vd.c. or 230 V~ 2A max. Ideal for controlling and measuring heating appliances, wallboxes and electric vehicle charging stations, ventilation systems, irrigation systems and any other device with a control dry contact. Not suitable for shutter automation. A toroid is supplied, for the measurement of the current absorbed by the load, max 80 A. Function management through the Home + Control App, compatible with load management module FC80GCS. 1 DIN module. 100-240 V~ power supply 50/60 Hz.
○ 4141PC	Connected PLUG & PLAY socket  Connected plug&play socket - Directly connected to an existing socket, it allows remote control of all the connected electrical appliances. It also monitors the instantaneous, daily and monthly consumption. Compatible with all the devices with power up to 16 A 3680 W (with overload protection). It can be associated to wireless light controls. Power supply 110-230 V~ - white Shuko standard socket
<input type="checkbox"/> YW4141AC <input checked="" type="checkbox"/> YG4141AC <input checked="" type="checkbox"/> YD4141AC	Connected socket  2P+E 16 A 250 V~ German standard connected socket. It allows remote control of electric devices and also to monitor their consumption (instantaneous, daily, monthly). It is also possible to receive notifications that can be configured. Compatible with all the electric devices with power up to 16 A 3680W (with overload protection). Integrated with a 2-module support, it can be installed instead of an existing socket in a 40 mm deep box. Screw fixing and connection using automatic clamps It has a blue LED that lights up when the socket is ON and that can be configured by means of the Home + Control APP. It can be associated to one or more wireless light controls. Power supply 110-230 V~ - 2 modules
<input type="checkbox"/> YW4142AC <input checked="" type="checkbox"/> YG4142AC <input checked="" type="checkbox"/> YD4142AC	 As above. French/belgian std. - 2 modules

Light Now with Netatmo

wireless controls for scenarios management



YW4570CW



YG4570CWG



YD4570CWI



YG4574CWG






YD4574CWI









YD4575CW



3528C

Item	Wireless Home/Away scenario controls
<input type="checkbox"/> YW4570CW <input checked="" type="checkbox"/> YG4570CW <input checked="" type="checkbox"/> YD4570CW	 <p>Wireless Home/Away scenario controls. It is equipped with 2 buttons for activating Home/Away scenarios. Scenarios can be customized by the Home + Control app. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules</p>
<input type="checkbox"/> YW4570CWG <input checked="" type="checkbox"/> YG4570CWG <input checked="" type="checkbox"/> YD4570CWG	 <p>As above. No-Battery Switch. - 2 modules</p>
<input type="checkbox"/> YW4570CWI <input checked="" type="checkbox"/> YG4570CWI <input checked="" type="checkbox"/> YD4570CWI	 <p>Wireless Home/Away scenario controls. It is equipped with 2 buttons for activating Home / Away scenarios. Scenarios can be customized by the Home + Control app. It can be installed in any flush-mounted box without any wiring. The battery can be replaced without removing it from the supporting frame. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 1 module</p>

Item	Wireless Wake Up / Sleep scenario controls
<input type="checkbox"/> YW4574CW <input checked="" type="checkbox"/> YG4574CW <input checked="" type="checkbox"/> YD4574CW	 <p>Wireless Wake Up / Sleep scenario controls. It is equipped with 2 buttons for activating Wake Up / Sleep scenarios. Scenarios can be customized by the Home + Control app. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules</p>
<input type="checkbox"/> YW4574CWG <input checked="" type="checkbox"/> YG4574CWG <input checked="" type="checkbox"/> YD4574CWG	 <p>As above. No-Battery Switch. - 2 modules</p>
<input type="checkbox"/> YW4574CWI <input checked="" type="checkbox"/> YG4574CWI <input checked="" type="checkbox"/> YD4574CWI	 <p>Wireless Wake Up / Sleep scenario controls. It is equipped with 2 buttons for activating Wake Up / Sleep scenarios. Scenarios can be customized by the Home + Control app. It can be installed in any flush-mounted box without any wiring. The battery can be replaced without removing it from the supporting frame. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 1 module.</p>

Item	Wireless 4 scenario controls
<input type="checkbox"/> YW4575CW <input checked="" type="checkbox"/> YG4575CW <input checked="" type="checkbox"/> YD4575CW	 <p>Wireless 4 scenarios control. It's equipped with 4 buttons for activating of scenarios 1,2,3 and 4. Scenarios can be customized by the Home+ Control app. Surface installation with repositionable stickers (supplied) or onto a flushmounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules.</p>
<input type="checkbox"/> YW4575CWG <input checked="" type="checkbox"/> YG4575CWG <input checked="" type="checkbox"/> YD4575CWG	 <p>As above. No-Battery Switch. - 2 modules</p>
<input type="radio"/> 3528C	 <p>Pocket remote control 4 scenarios Pocket remote control 4 scenarios. It allows to add a wireless remote control in your system. Is equipped with 4 keys for the activation of the 1,2,3 and 4 scenarios. The scenarios can be activated and customized by the Home + Control app. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years.</p>

Light Now with Netatmo



XW8003



XM8003




XG8003



XW800.3W



3460IR



0.489 10

Connected thermostat for air conditioning

Item
<input type="checkbox"/> XW8003
<input type="checkbox"/> XM8003
<input checked="" type="checkbox"/> XG8003
<input type="checkbox"/> XW8003W



The Smarter AC with Netatmo connected thermostat, together with the Home + Control APP, is a device which allows to precisely and accurately adjust and monitor the temperature in the rooms; all the programming and most of the functions can be easily and intuitively performed using the App. Thanks to its Wi-Fi connection, Smarter AC can be programmed and controlled remotely; it can also display the temperature, fan speed and humidity measured in the room. The temperature level can be set locally for manual operation and Boost mode can be activated. The Boost forces the switching on of the system for a limited time (15, 30 or 45 minutes) irrespective of the measured and programmed temperature.

Smarter AC with Netatmo can also be controlled with Google, Amazon Alexa and Apple Home Kit voice assistants.

- Power supply 110 to 240 V~ , 50/60 Hz;
- 2 W max absorption;
- Maximum cable section 1 x 1.5 mm²;
- Operating temperature 5 to 40 °C;
- 1-switching contact output free of 5(2)A potential.

- Type of operation 1BU
- Pollution index 2
- Rated pulse voltage 4 kV
- Wireless device in compliance with 802.11b/g/n standard, frequency 2.4 - 2.4835 GHz, transmission power < 20 dBm. WEP/WPA/WPA2 safety protocol IPv4.
- Radio link: short range communication, frequency 868MHz/915MHz, transmission power < 25mW e.r.p. (*).

Types of installation

- flush mounted, on boxes item 503E or 500 (for item 500 use the wall dowels)
- plasterboard, on boxes item PB503 and PB502

Available in three colours: white (XW8003), sand (XM8003) and black (XG8003).



Features: as XW8003. Installation: on the wall, using screws and dowels suitable for the installation surface (brickwork, plasterboard, tiles etc.). It is available only in white colour.

Actuator for fan coil unit

Item
○ 0 489 10
○ 3460IR



This actuator can be used in combination with Smarter AC with Netatmo on thermoregulation installations, to control different load types according to requirements.

This DIN actuator can control:

- 2-pipe fan coil unit with On/Off valve
- 2-pipe fan coil unit with 3-way valve
- 2-pipe fan coil unit with 0-10 V valve
- 4-pipe fan coil unit with two On/Off valves
- 4-pipe fan coil unit with two 3-way valves
- 4-pipe fan coil unit with two 0-10 V valves
- 3-speed fan
- 1 0-10 V fan

IR interface for air conditioning unit



Connected IR emitter for air conditioning. The installation with Smarther AC allows the smart management of an A/C unit with infrared. The device size is 60x60x30 mm, white color and it is provided with a white cable (length 1.5 m). It supports both power sources: 5÷12 Vd.c. and 110-240V ~ 50/60Hz. It communicates with Smarther AC through RF 2.4 GHz: thanks to its features, the emitter can be placed on the receiver of the A/C unit, ensuring perfect communication.



Note(*): 868MHz/915MHz radio link not available in Malaysia, China, Japan, Singapore and Taiwan.

Light Now with Netatmo

connected thermostats



XW8002



XM8002



XG8002



XW8002W

Connected thermostats

Item

☐ XW8002

☐ XM8002

☒ XG8002

☐ XW8002W



The Smarter with Netatmo connected thermostat, together with the dedicated HOME+CONTROL APP, is a device which allows you to adjust and monitor the temperature in the rooms precisely and accurately; all the programming and most of the functions are performed simply and intuitively using the APP. Thanks to its Wi-Fi connection, Smarter with Netatmo can be programmed and controlled remotely; it can also display the temperature and humidity measured in the room. The temperature level can be set locally for manual operation and the Boost mode can be activated. The Boost forces the switching on of the system for a limited time (30, 60 or 90 minutes) independent of the measured and programmed temperature. It's also possible to set a different temperature in each room of the house for the maximum comfort, thanks to its compatibility with Netatmo's smart radiator valves. Smarter with Netatmo can also be controlled with Google, Amazon Alexa and Apple Home Kit voice assistants.

Features:

- 110 ÷ 230 V~, 50/60 Hz power supply;
- 2 W max absorption;
- maximum cable section 1 x 1.5 mm²;
- temperature measurement 5 ÷ 40 °C;
- temperature set-point 5 ÷ 40 °C,
- increase of 0.5 °C;
- 1-contact output in switching free of potential 5(2) A.
- Radio link: short range communication, frequency 868MHz/915MHz, transmission power < 25mW e.r.p. (*).

Types of installation:

- flush mounted, on boxes item 503E or 500 (for item 500 use the wall dowels)
- plasterboard, on boxes 2 module e 3 module

It is available in three colours: white (XW8002), sand (XM8002) and black (XG8002).





```
features: as ..8002.
```

Installation: on the wall, using screws and dowels suitable for the installation surface (brickwork, plasterboard, tiles etc.). It is only available in white.

Note(*): 868MHz/915MHz radio link not available in Malaysia, China, Japan, Singapore and Taiwan.



Light Now MyHOME



Connected controls for the Smart Home

SECTION 3

Light Now MyHOME


Connected controls for the smart home, which communicate via SCS BTicino bus.

How to choose devices for the composition of the electrical system

SECTION 3



















SECTION 1



Type of system	Catalog section
Light Now standard system (Switches, sockets and cover plates for the residential electrical system)	1
Light Now with Netatmo (Connected controls for the smart home, which communicate via radio)	2 + 1
Light Now MyHOME (Connected controls for the smart home, which communicate via SCS BTicino bus)	3 + 1
Light Now KNX (Connected controls for the smart home, which communicate via KNX standard bus)	4 + 1

MyHOME

Table of choice

Functions	Control devices (27 Vd.c. by BUS)			
 <p>Internet connection</p>	 <p>Web server F460</p>	 <p>Classe 300EOS 44842 (white) 44884 (black)</p>	 <p>works with Google Home</p> <p>works with alexa</p>	 <p>Home + Control</p>  <p>Home + Project</p>
 <p>Shutters and electrical doors</p>	 <p>Control devices Y4652M2 (2 modules)</p>	 <p>Control devices Y4652M3 (3 modules)</p>	 <p>Basic contact interface 3477</p>	 <p>DIN contact interface F428</p>
 <p>Energy management and monitoring</p>	 <p>Energy meter F520</p>	 <p>Impulse counter interface 3522N</p>	 <p>Load control central F521</p>	 <p>Energy data logger F524</p>

NOTE: complete the installation with the appropriate power supply item E56 or item E49.

Actuator devices (BUS: 27 Vd.c. - Power line: 230 V~)



Actuator/control
Y4672M2L



Relay actuator
3476



Relay actuator
F411/1NC



1-output dimmer
F413N



2 relay actuator
F411U2



4 relay actuator
F411/4



Multi-load dimmer
F416U1 (1 output)
F418U2 (2 output)



ON/OFF actuator
«zero crossing»
BMSW1003
BMSW1005



F429G (DALI-2 gateway)
F429D (DALI-2 dimmer)
F429 (DALI dimmer)



Actuator/control
Y4672M2S



2 relay actuator
F401



2 relay actuator
F411U2



4 relay actuator
F411/4



Actuator for management
of the load F522



1 relay actuator "zero crossing" for
management of the load F523



2 relay actuator
F430/2



4 relay actuator
F430/4



8 relay actuator
F430R8



Actuator with 3
relays and 2x0-10 Volt
output F430R3V10



Actuator with 2x0-10 Volt
Outputs F430V10



Light Now MyHOME

integration and control



F460



F461



F459

Item
○ F460

MyHOME Server



The new SCS server is a device designed to interact with the MyHOME system; It allows to create and realize high level installation to manage BUS SCS Smart Home solutions occupying less DIN modules (4), key for MyHome business to have a solution optimized for the cabinet. It has natively integrated the capability of humidity management and It natively supports 175 addresses with the possibility of extension by adding max 2 BT-F422A interfaces SCS. The Server is suitable for:

- devices association during the system starting-up by the installer in Home+Project app. Concerning the Lights, Automation, Temperature Control and Energy systems, the system is started via the Server directly using the Home + Project application (It allows you to configure the system also without internet).
- for the local and remote management of the functions by the user with the specific Home + Control app for Android and iOS smartphones and vocal compatibility with Alexa® e Google® is possible to manage the Myhome System or 3rd party devices (ex. Interact with lamps Philips Hue®, Lix®, ...). It can perform customisations and create scenarios for managing the MyHOME system.

The server can be combined with a physical interface used as VDE internal unit and Touchscreen to control the installation (HomeTouch) - 4 DIN modules.

○ F461

MyHOME Server 3rd Parties integration



A dedicated version of 4 DIN server open to third party that supports the use and integration of the 3rdParties systems. It has native protocol to provide local integration in 3rd party systems, for advanced Home Automations systems like for instance RTI, Crestron, Control4, Savant with high value and complexity. Use the Home + Project app to start configuring the server, while for the usage it will be not Home + Control but the 3rd parties app. It cannot be used on the same installation with F460.

○ F459


Driver manager



Integration platform with other brand systems - 6 DIN modules
It requires the installation of specially designed driver for the integration of the system.

Contact the BTicino System Integration Service to check the feasibility of specific integrations and to request the licence needed to use the Driver manager.

System with web server F460 and use of Hometouch as a video internal unit.



Light Now MyHOME

integration and control



344842



344844



346020

Item
○ 344842
○ 344884

CLASSE 300EOS with Netatmo connected video internal unit



2 wires/Wi-Fi handsfree connected video internal unit with built-in Amazon Alexa voice assistant, 5" vertical touch screen LCD display and video door entry answering machine. It has a physical key for door lock release and capacitive keys for the control of the main video door entry functions: handsfree communication, entrance panel activation / camera scrolling and Favourite key (can be configured to activate the quick actions most frequently used – e.g. additional door locks, staircase light control, intercom). There are notification LEDs for: Wi-Fi network connection status, info / notifications and call exclusion. It is possible to easily interact with the built-in Alexa voice assistant, either using the dedicated capacitive keys or with your voice, and activate several functions, such as the video door entry functions, Smart Home, scenarios, reminders etc. Using the touch display, it is possible to access the notification list, as well as your favourite door entry, security and Smart Home controls (if any). The device must be configured by physically connecting the configurators or using the menu, which will give better possibilities of customisation of associated functions and texts. Thanks to the Wi-Fi connection, you can associate the video internal unit to the Home + Security App (available for Android and iOS). The App allows to use the main video internal unit functions (receiving calls, door lock release, display of the event timeline and activation of the entrance panel/camera cycling). Through the Home + Security App, it is also possible to manage the products of the Netatmo security range (outdoor and indoor cameras, door and window sensors, indoor siren and smoke detector). This allows you to quickly and easily create a Smart security system. The device also allows to create and manage Smart Home functions using the wired SCS BUS solution, without the need for adding dedicated webserver. Wall mounted installation using the supplied bracket Possibility of Wi-Fi connection or using RJ45 ethernet cable with the dedicated accessory 344844.


As above - black

Ethernet accessory




Accessory cable for wired connection of Classe 300EOS with Netatmo video internal unit via RJ45 Ethernet cable. To be purchased separately.

2 DIN Additional power supply



Additional power supply to be used to supply entrance panels and internal units locally. 2 DIN modular enclosure. Power supply 230 V~ at 50-60 Hz. The output provides 27 Vdc continuous low voltage, with maximum current of 600 mA and it is protected on the PRI side (with fuse) against overload and short circuit. It is a SELV double insulation safety device.

System with Classe 300EOS with Netatmo as server as an alternative to the server item F460




Light Now MyHOME




integration and control



3488



3487

Item	
<input type="radio"/> 3488	<div><p>HOMETOUCH - Touch Screen 7" for the management of all MyHOME functions, that can be integrated with the video door entry system and with indoor and outdoor Netatmo cameras, to be used as connected internal unit. To use the home automation functions, configuration is not necessary. It is possible to display the MyHOME system status and control the integrated functions (lights, automation, scenarios, burglar alarm, temperature management, Nuvo music system, ...). Thanks to the "DOOR ENTRY for HOMETOUCH" application, available both for Android and iOS operating systems, it is also possible to manage the video door entry functions of a BTicino 2 wires system using the 7" capacitive display or the Smartphone. Flush mounted installation with box for masonry walls (item 3487) or wall mounted installation with the supplied metal bracket. Tech grey.</p></div>
<input type="radio"/> 3488W	<div><p>As above - white</p></div>
<input type="radio"/> 3487	<div><p>Box for flush mounted installation of the HOMETOUCH Touch screen item 3488 and 3488W. Width 197 mm, height 148 mm and depth 52 mm.</p></div>
<input type="radio"/> 3487AP	<div><p>Support for flush mounted installation on plasterboard walls of the HOMETOUCH Touch screen item 3488 and 3488W.</p></div>



Y4652M2









Y4652M3









Y4672M2L
Y4672M2S


F428




3477

Item	Control devices	Item	Actuator/control for lights and generic loads
○ Y4652M2	 Based on the selected configuration, the device can manage up to: - 4 lights ON/OFF functions and adjustment of a dimmer load - 2 Shutter UP/DOWN and advanced functions - 4 Scenarios and load & force control - VDE control call to the floor, staircase light switching on and door lock activation functions. 2 modules to be equipped with 1 or 2 modules key covers, support frames and plates.	○ Y4672M2L	 Actuator/control with 2 independent relays for single or double loads: the device can be also configured to manage a remote actuator with the same functions of the Y4652M2 controls - 2 modules. To be completed with 1 or 2 modules key covers, support frames and plates.
○ Y4652M3	 Based on the selected configuration, the device can manage up to: - 6 lights ON/OFF functions and adjustment of a dimmer load - 3 Shutter UP/DOWN and advanced functions - 6 Scenarios and load & force control - VDE control call to the floor, staircase light switching on and door lock activation functions. 3 modules to be equipped with 1 or 2 modules key covers, support frames and plates.	○ Y4672M2S	 Shutter actuator with relay 2 A 250 VA. In addition to the monostable and bistable UP/DOWN function, the actuator also places the rolling shutter in a stored (PRESET) position. The device can be also configured to manage a remote actuator - 2 modules. To be completed with 1 or 2-modules key covers, support frames and plates.
○ 3477	 Basic module control interface with 2 independent contacts for the control of 2 actuators for single function loads, or 1 actuator for double function loads (shutters) - the inputs accepts two traditional switches or pushbuttons with NO and NC contact, or a traditional two-way switch, or interlocked pushbuttons.		
○ F428	 As above - 2 DIN modules		

LOADS THAT CAN BE DRIVEN (230 V~ 50/60 Hz)							
Actuators	Type						
							
	Energy saving incandescence and halogen lamps	LED lamps	Linear fluorescent lamps ¹⁾	Compact fluorescent lamps	Electronic transformers ³⁾	Ferromagnetic transformers ^{2) 3)}	Reducer motors for shutters ⁴⁾
Y4672M2L	1380 W	250 W Max 2 lamps	250 VA	250 W Max 2 lamps	460 W	460 VA	460 W
Y4672M2S	-	-	-	-	-	-	2 A 250 V~

Notes:

- 1) Power factor corrected fluorescent lamps, discharge lamps.
- 2) Account must be taken of the transformer yield to calculate the effective power of the load connected to the actuator. For example if a dimmer is connected to a 100 VA ferromagnetic transformer with yield 0.8, the effective power of the load will be 125 VA.
- 3) The transformer must be loaded at its rated power and however never less than 90% of this power. It is preferable to use a single transformer rather than several transformers in parallel. For example it is better to use a single 250 VA transformer with 5 50W spotlights connected rather than use 5 50 VA transformers in parallel each with a 50 W spotlight.
- 4) The  symbol on the actuators refers to the shutter reducer motors.

Light Now MyHOME

key covers

1-FUNCTION non-silk-screen printed key covers



YD4915MH YW4915MH2 YG4915MH

Non silk-screen printed key covers - 1 function

Color	1 module	2 modules
	Item	Item
□ White	YW4915MH	YW4915MH2
■ Stone	YG4915MH	YG4915MH2
■ Dark	YD4915MH	YD4915MH2

2-FUNCTION non-silk-screen printed key covers



YD4911MH YW4911MH2 YG4911MH

Non silk-screen printed key covers - 2 functions

Color	1 module	2 modules
	Item	Item
□ White	YW4911MH	YW4911MH2
■ Stone	YG4911MH	YG4911MH2
■ Dark	YD4911MH	YD4911MH2

1-FUNCTION silk-screen printed key covers



YG4915MHB YW4915MH2AD YD4915MHF

Silk-screen printed key covers with symbols - 1 function

Description	Color	1 module	2 modules
		Item	Item
Control of 1 dimmer	□ White	YW4915MHAD	YW4915MH2AD
	■ Stone	YG4915MHAD	YG4915MH2AD
	■ Dark	YD4915MHAD	YD4915MH2AD
Stop	□ White	YW4915MHAE	-
	■ Stone	YG4915MHAE	-
	■ Dark	YD4915MHAE	-
Staircase light	□ White	YW4915MHB	YW4915MH2B
	■ Stone	YG4915MHB	YG4915MH2B
	■ Dark	YD4915MHB	YD4915MH2B
Key	□ White	YW4915MHF	YW4915MH2F
	■ Stone	YG4915MHF	YG4915MH2F
	■ Dark	YD4915MHF	YD4915MH2F
Doorbell	□ White	YW4915MHD	YW4915MH2DM
	■ Stone	YG4915MHD	YG4915MH2DM
	■ Dark	YD4915MHD	YD4915MH2DM

Dimmer	Stop	Staircase light	Key	Doorbell	On - Off	Up - down
On - Off plus regulation	Regulation + up and - down	Home-away	Day-night	Scenario N° 1 - 2	Scenario N° 3 - 4	2 Dimmer

□ White colour ■ Stone colour ■ Dark colour ○ Neutral item

2-FUNCTION silk-screen printed key covers



YD4911MHAL YG4911MHAG YW4911MH2AJ

Silk-screen printed key covers with symbols - 2 functions

Description	Color	1 module	2 modules
		Item	Item
Control of 2 dimmers	□ White	YW49112MHAD	YW49112MH2AD
	■ Stone	YG49112MHAD	YG49112MH2AD
	■ Dark	YD49112MHAD	YD49112MH2AD
On - Off	□ White	YW4911MHAG	YW4911MH2AG
	■ Stone	YG4911MHAG	YG4911MH2AG
	■ Dark	YD4911MHAG	YD4911MH2AG
Up - down	□ White	YW4911MHAH	YW4911MH2AH
	■ Stone	YG4911MHAH	YG4911MH2AH
	■ Dark	YD4911MHAH	YD4911MH2AH
On - Off plus regulation up and down	□ White	YW4911MHAJ	YW4911MH2AJ
	■ Stone	YG4911MHAJ	YG4911MH2AJ
	■ Dark	YD4911MHAJ	YD4911MH2AJ
Regulation + up and - down	□ White	YW4911MHAD	-
	■ Stone	YG4911MHAD	-
	■ Dark	YD4911MHAD	-
Home-away	□ White	YW4911MHAJ	YW4911MH2AJ
	■ Stone	YG4911MHAJ	YG4911MH2AJ
	■ Dark	YD4911MHAJ	YD4911MH2AJ
Day-night	□ White	YW4911MHAL	YW4911MH2AL
	■ Stone	YG4911MHAL	YG4911MH2AL
	■ Dark	YD4911MHAL	YD4911MH2AL
Scenario N° 1 - 2	□ White	YW4911MHAM	-
	■ Stone	YG4911MHAM	-
	■ Dark	YD4911MHAM	-
Scenario N° 3 - 4	□ White	YW4911MHAN	-
	■ Stone	YG4911MHAN	-
	■ Dark	YD4911MHAN	-

Light Now MyHOME

actuators for lights, shutters and different loads



Item	Light control/actuator	Item	Actuators for centralisations
○ 3476	1 relay actuator - for single loads: 2 A resistive or incandescence lamps, 2 A cosφ 0.5 for ferromagnetic transformers - a traditional pushbutton with NO contact accepted in input	○ BMSW1003	ON/OFF actuator, 4 independent outputs with maximum load 16 A at 230 V~, clamp connection and RJ45, IP20 protection index, power supply 100/240 V~ 50/60 Hz, pushbuttons for load direct control - zero-crossing function - 6 DIN modules
○ F411U2	Actuators for centralisations Actuator with 2 independent relays – for single and double loads: 10 A resistive and 6 A incandescence lamps, 500 W for reducer motors, 2 A cosφ 0.5 for ferromagnetic transformers and 250 W for fluorescent lamps - logic relay interlock via configuration - it has "Zero crossing" technology - 2 DIN modules	○ BMSW1005	ON/OFF actuator, "Zero Crossing" technology, 8 independent outputs with maximum load 16 A at 230 V~, clamp connection, IP20 protection index, power supply 100/240 V~ 50/60 Hz, pushbuttons for load direct control - 10 DIN modules
○ F411/4	Actuator with 4 independent relays - for single, double or mixed loads: 2 A resistive, 2 A incandescence lamps, 500 W for reducer motors, 2 A cosφ 0.5 for ferromagnetic transformers and 70 W for fluorescent lamps - logic relay interlock via configuration - 2 DIN modules	○ F401	Actuator for shutters Actuator with 2 internal relays and 4 pushbuttons. In addition to monostable and bistable UP/DOWN operation, the actuator also places the shutter in a stored (PRESET) position - 2 DIN modules
○ F411/1NC	Actuator with 1 two-way NC relay for single loads, 16 A resistive, 10 A for incandescence lamps, and 4 A for fluorescent lamps. At switch on, the contact of the device is always closed (ON status), and it opens when an OFF control is sent. In this way, if there is no power input from the BUS, the device will remain in the ON status, keeping the load ON - 2 DIN modules		

LOADS THAT CAN BE DRIVEN (250 V~ 50/60 Hz)

Actuators	Type						
	Energy saving incandescence and halogen lamps	LED lamps	Linear fluorescent lamps ¹⁾	Compact fluorescent lamps	Electronic transformers ³⁾	Ferromagnetic transformers ^{2) 3)}	Reducer motors for shutters ⁴⁾
3476	2 A 460 W	40 W Max 1 lamp	- -	40 W Max 1 lamp	- -	2 A cosφ 0,5 460 VA	- -
F411U2	10 A 1380 W	250 W Max 4 lamps	4 A 230 W	250 W Max 4 lamps	4 A 230 W	4 A cosφ 0,5 460 VA	2 A 460 W
F411/4	2 A 460 W	70 W Max 2 lamps	0.3 A 70 W	70 W Max 2 lamps	0.3 A 70 W	2 A cosφ 0,5 460 VA	2 A 460 W
BMSW1003	16 A 3680 W	2.1 A 500 VA	10 X (2 X 36 W) 4.3 A	1150 W 5 A	16 A 3680 W	16 A 3680 W	- -
BMSW1005	16 A 3680 W	2.1 A 500 VA	4.3 A 10X2X36 W	5 A 1150 VA	16 A 3680 W	16 A 3680 W	- -
F401							2 A 250 V~
F411/1NC	10 A 2300 W	500 W Max 10 lamps	4 A 920 W	500 W Max 10 lamps	4 A 920 W	4 A cosφ 0,5 920 VA	

Notes:


1) Power factor corrected fluorescent lamps, discharge lamps. 2) Account must be taken of the transformer yield to calculate the effective power of the load connected to the actuator. For example if a dimmer is connected to a 100 VA ferromagnetic transformer with yield 0.8, the effective power of the load will be 125 VA. 3) The transformer must be loaded at its rated power and however never less than 90% of this power. It is preferable to use a single transformer rather than several transformers in parallel. For example it is better to use a single 250 VA transformer with 5 50W spotlights connected rather than use 5 50 VA transformers in parallel each with a 50 W spotlight. 4) The symbol on the actuators refers to the shutter reducer motors.

Light Now MyHOME

dimmer actuators for lights and different loads



F413N



F429



F416U1






F418U2






F429G










F429D


Item	Dimmers for centralisations
○ F413N	 1-output dimmer to supply fluorescent lamps or LED sources with input 1-10 V for single loads up to 2.5 A at 230 V~ – type of screw connection - power supply 27 Vd.c. – absorption 30 mA – max 10 ballast that can be connected (clamps 1-2) - with pushbutton for load direct control - version for fastening on DIN rail - 2 modules
○ F416U1	 Multi-load dimmer, 1 output with maximum load 4.3 A at 230 V~, clamp connection and RJ45, IP20 protection index, power supply 100/240 V~ 50/60 Hz, pushbutton for load direct control - 6 DIN modules
○ F418U2	 Two-channel dimmer for the management of dimmer LEDs, dimmer compact fluorescent lamps (CFL), energy saving halogen lamps and electronic transformers at 110-230V. Possibility of parallelisation of the two channels to increase the maximum power which can be managed. power supply 27 Vd.c., absorption 18 mA - version for fastening on DIN rail - 4 modules

Item	Devices for DALI lamps management
○ F429G	 DALI-2 Gateway - The device is an interface between MyHOME/Lighting Management systems and devices driven using the DALI (Digital Addressable Lighting Interface) protocol. It has 1 independent outputs to manage up to 64 ballast DALI2. The functionalities supported are: ON/OFF, dimmer, RGBW (colour and tunable white) e phase in-out. The device can be installed in a MyHOME system through H+P app configuration. Suitable in houses where the installation is made with all Dali2 lamps.
○ F429D	 DALI-2 dimmer - The device is an interface between MyHOME/Lighting Management systems and devices driven using the DALI (Digital Addressable Lighting Interface) protocol. It has 2 independent outputs to control up to 32 ballasts (2 groups of 16 DALI-2 lamps). The functionalities supported are: ON/OFF, dimmer, RGBW (colour and tunable white) e phase in-out. The device can be installed in a MyHOME system through H+P app configuration. Suitable for installations with few DALI-2 lamps.
○ F429	 DALI dimmer with 8 independent outputs for the connection of up to 16 DALI reactors for each output – 230 V~ power supply 50/60 Hz; 110 - 240 Vd.c. – absorption 5 mA - with pushbutton for load direct control - version for fastening on DIN rail - 6 modules

LOADS THAT CAN BE DRIVEN (230 V~ 50/60 HZ)

Actuators	Type						
							
	Energy saving incandescence and halogen lamps	LED lamps	Linear fluorescent lamps ¹⁾	Compact fluorescent lamps	Electronic transformers ³⁾	Ferromagnetic transformers ^{2) 3)}	Reducer motors for shutters ⁴⁾
F413N	-	-	2 A 460 W ⁵⁾ Max 10 ballast, type T5, T8, compact or driver for LED	-	-	-	-
F416U1	4.3 A 40 - 1000 W	-	-	-	4.3 A 40 - 1000 W	4.3 A 40 - 1000 W	-
F418U2	2x300 W	2x300 VA	-	2x300 VA	2x300 VA	2x300 VA	-
F429	SCS/DALI dimmer interface - 8 x16 ballast						
F429G	SCS/DALI2 gateway – up to 64 ballast DALI2						
F429D	SCS/DALI2 dimmer – up to 64 ballast DALI2						






Notes:

1) Power factor corrected fluorescent lamps, discharge lamps. 2) Account must be taken of the transformer yield to calculate the effective power of the load connected to the actuator. For example if a dimmer is connected to a 100 VA ferromagnetic transformer with yield 0.8, the effective power of the load will be 125 VA. 3) The transformer must be loaded at its rated power and however never less than 90% of this power. It is preferable to use a single transformer rather than several transformers in parallel. For example it is better to use a single 250 VA transformer with 5 50W spotlights connected rather than use 5 50 VA transformers in parallel each with a 50 W spotlight. 4) The  symbol on the actuators refers to the shutter reducer motors. 5) Only compatible with lamps with 1/10 V ballast.

Light Now MyHOME

lighting/movement sensors



Item	Lighting/movement sensors	Item	Remote control and configuration gateway
○ BMSE3001	 <p>Passive infrared SCS sensor for the detection of movement and the lighting level. Ceiling flush mounted installation using springs or installation boxes; surface installation using surface installation box, item 048875; IP20 protection index; RJ45 clamp connection; 8 m (50 m²) diameter coverage area for a 2.5 m installation height, maximum installation height 6 m; 27 V.d.c. power supply from bus, absorption 12 mA; regulation with basic/advanced remote control (BMSO4003 and BMSO4001) or through configuration software, of the lighting level, from 5 to 1275 LUX, of the time delay, from 30 s to 255 h, and of the main operating parameters; Push&Learn pushbutton</p>	○ 0 882 40	 <p>The Gateway allows you to adjust the time delay, the brightness threshold and the detection sensitivity. Possibility to store, share, prepare all of the product settings for a construction site advance. Possibility of duplicating the parameters of a product 0 882 40. Works with the App "Legrand Close Up" available on Google Play and Apple Store via Bluetooth Low Energy technology for smartphone. Allows the configuration of windows, management systems lighting and emergency lighting units and offers advanced features to facilitate the management of facilities.</p>
○ BMSE3003	 <p>Double technology SCS sensor: passive infrared for the detection of presence and the lighting level. Ceiling flush mounted installation using springs or installation boxes; surface installation using surface installation box, item 048875; IP20 protection index; RJ45 clamp connection; 8 m diameter (50 m²) infrared coverage area for a 2.5 m installation height, 11 mm diameter (95 m²) ultrasound coverage area for a 2.5 m installation height, maximum installation height 6 m; 27 V.d.c. power supply from BUS, absorption 17 mA; regulation with basic/advanced remote control (BMSO4003 and BMSO4001), or through configuration software, of the lighting level, from 5 to 1275 LUX, of the delay, from 30 s to 255 h, and of the main operating parameters; Push&Learn pushbutton</p>	○ BMSO4003	 <p>The basic configuration remote control, with IR transmitter, adjusts the main operating parameters of: Switch Sensor, Green Switch and SCS compatible sensors. Modification of parameters only possible for preset values, battery recharge not available</p>
<input type="checkbox"/> YW4658 <input checked="" type="checkbox"/> YG4658 <input checked="" type="checkbox"/> YD4658	 <p>Green Switch: dual technology presence sensor, passive infrared and ultrasound (PIR + US), suitable for the presence detection in the work areas (offices, meeting rooms). Equipped with manual on/off switch. Mode of operation (automatic or manual), delay time (from 5s to 59min) and brightness threshold (from 20 to 1275 lux) settable by means of advanced/basic configuration remote control BMSO4003), physical or virtual configuration. 2 modules.</p>	○ 0 488 75	<p>Installation accessories</p> <p>Ceiling mounted box compatible with the sensors: BMSE3001 and BMSE3003, IP20 protection index, dimensions Ø 100 x 50 mm</p>

Features of the lighting/movement sensors

SCS sensors	BMSE3001	BMSE3003	JYW/YG/YD4658
Installation	ceiling flush mounted		flush mounted
Type of operation	AUTO/ECO/WALKTHROUGH		AUTO/ECO/ WALKTHROUGH
Sensor technology	PIR	PIR+US	PIR+US
Power supply	27 V d.c. from Bus		27 V d.c. from Bus
Protection index	IP20		
Coverage area at 2.5 m	Ø 8 m	Ø 11 m	8 m x 6 m
Coverage angles (v/h)	90/360°		90°/180°
Lighting level	5 lux - 1275 lux		20 - 1275 lux
Switching off delay	30 s - 255 h 59 min 59 sec		30 sec – 255h 59 min 59 sec
Factory adjustments	300 lux - 15 min		300 lux - 15 min
Connection type	RJ45 connector		Clamp

Light Now MyHOME

temperature control




H4691



3454




F430/2










F430R8



F430V10











Item	Thermostat
○ H4691	 <p>Probe with backlit display that controls the temperature of an individual zone. It features an input for the connection of a contact line (e.g. window contact). It can be used for the management of different types of systems, and the adjustment of the fan speed when fan coils are used. Possibility of automatic operation (summer/winter), with compatible systems - 2 modules</p>

Item	Probe without display
○ 3454	 <p>Temperature probe in basic module with wired sensor - to be associated to the temperature sensor item 3457 and Vantage probe item 8051</p>
○ 3457	Accessories  <p>Temperature probe to be associated to the probe item 3454</p>
○ F430/2	Actuators for valve control  <p>Actuator with 2 independent relays – for single and double loads: 6 A resistive, 2A motor driven valves and pumps - configuration based logic relay interlock - 2 DIN modules</p>
○ F430/4	 <p>Actuator with 4 independent relays - for single, double or mixed loads: 4 A resistive, 1 A motor driven valves, pumps and fan coils - configuration based logic relay interlock - 2 DIN modules</p>
○ F430R8	 <p>Actuator with 8 independent relays for the control of on-off valves, motorised valves (open-close and three points), pumps and fan coils with 2 and 4 tubes - 4A resistive, 1A motor valves, pumps and fan-coils- SCS-bus connection - 4 DIN modules</p>
○ F430R3V10	 <p>Actuator with 3 independent relays and 2 x 0-10 Volts outputs for the control of fan coils with 2 and 4 tubes with proportional 0-10 Volt valves - 4A resistive, 1A fan coil - SCS-BUS connection - 4 DIN modules</p>
○ F430V10	 <p>Actuator with 2 x 0-10 Volt outputs for the control of 0-10 proportional valves - SCS-BUS connection - 2 DIN modules</p>

Light Now MyHOME

energy management


















Item	Consumption display	Item	Energy data logger - centralisation of energy consumption data
○ F520	 Meter for the measurement of electricity on a maximum of 3 lines, by connecting 3 toroids to the appropriate inputs. Version for fastening on DIN rail. The device is fitted with 1 toroid. Data visualization with Home+Control app. - 1 module.	○ F524	 Device for the centralisation of energy consumption data measured using meters with toroids, item F520, load control central units, item F521. The data can be displayed in appropriate integrated web pages by connecting the device to a network through the Ethernet port. It gives the possibility of configuring different tariffs, of downloading the data, and of adding up or subtracting the lines, as well as of performing multiplications by a certain factor. The device has a microSD slot for the backup of the data recorded, and OPENWebNet controls for the display of consumptions. Version for installation on DIN modules - 1 module - Power supply from BUS 27 V.
○ 3523	 Additional electricity meter toroid, item F520 and for actuator with sensor, item F522 for the measurement of the earth leakage current. Cable length 400 mm.		
○ 3522N	 Impulse counter interface for the data measurement from meters (water, gas, etc...) with impulse output. The values measured can be displayed on all the MyHOME user interfaces (HOMETOUCH and HOME+CONTROL App). Basic module version for hidden installation. Power supply from BUS 27 V.		
	Load control management		Accessories
○ F521	 Central unit for the management and control of the actuators of the load control system, to prevent the risk of detachment of the limiter of the electricity supplier. The central unit manages up to 63 loads, a contract power between 1.5 and 18 kW, and tolerance up to +/- 20%. It integrates an electricity meter for the controlled line. Version for fastening on DIN rail. The device is fitted with 1 toroid. Data visualization with Home+Control app. - 1 module	○ 3508BUS	 removable clamp for BUS connection - width 3.81 mm
○ F522	 Actuator with integrated current sensor for the measurement of the controlled load consumptions. 1 relay - 10 A for incandescence lamps and 4 A for fluorescent lamps or ferromagnetic transformers, and 500 W for compact fluorescent and LED lamps - Bistable relay with zero crossing for the Automation and/or Load control management functions. Version for fastening on DIN rail - 1 module. Earth leakage control by connecting the additional toroid, item 3523. Data visualization with Home+Control app.	○ 3508U2	 removable clamp 2 poles
○ F523	 1 relay actuator - for incandescence lamps and 4 A for fluorescent lamps or ferromagnetic transformers, and 500 W for compact fluorescent and LED lamps - bistable relay with zero crossing for the Automation and/or Load control management functions. Version for fastening on DIN rail Data visualization with Home+Control app. - 1 module.	○ 3508U3	 removable clamp 3 poles

Light Now MyHOME



power supply, accessory and cables



Item	SCS addresses extension interface
○ F422A	 2 Din modules Interface between SCS BUS based systems, dedicated just to the logic expansion of the address extension and not to all the functions supported with the previous BT-F422. It can be used with both, DIN server BT-F460 and Classe300EOS with Netatmo. Each interface can add 175 addresses, with a maximum of 2 interfaces allowed for installation (BT-F460 with max 2 F422A; Classe300EOS with max +1 F422A). By doing so thanks to this device you will be able to overcome the current limit of 175 addresses and configure huge installations with up to 525 addresses. No parameters to take into consideration because the assignment is automatic.
○ F422	SCS interface for different systems  Interface between SCS BUS based systems, dedicated to different functions - 2 lowered DIN modules
○ F420	Scenario Module  Device enabling to save 16 scenarios for Automation, Temperature control and Video door entry applications - 2 DIN modules
○ F425	Memory Module  Module used for saving the status of the actuators - to reset the light automation system in case of power cut - 2 lowered DIN modules.

Item	Power supply
○ E56	 Power supply with input voltage 110 - 240 V~ @ 50 - 60 Hz. It provides two output power supplies in very low safety voltage (one of 27V DC 1.2A on the SCS terminals, one of 28.5V c.c. on terminal 1 - 2) to be used alternatively e NOT simultaneously. It can be used also as an additional power supply (output 1 - 2) for the local power supply of the devices automation (in this case it is not possible use no other output). The device is electronically protected against overload and short circuit. It is a device SELV double insulation safety device - Overall dimensions 6 DIN modules.
○ E49	 Compact power supply for Temperature control and Automation systems - input 230 V~, output 27 Vdc - maximum power delivered 600 mA - 2 DIN modules.
○ L4669	Connection cables  Sheathed pair made up of 2 flexible wires with unshielded plaited sheath - insulation 300/500 V - complies with standards CEI 46-5 and CEI 20-20 - coil length 100 metres
○ L4669/500	as above - in 500 m coils 
○ L4669KM1	As above - reel length 1000 m 
○ 336905	As above - low toxicity cable without halogens - ideal for application in environments where fire hazard safety is critical - coil length 200 metres 
○ 336904	Specific cable with 2 twisted conductors. It can be installed in underground piping, in accordance with standards (CEI 20-13 and CEI 20-14). It ensures the best performance in video systems (higher distance between EP and Handset when compared with other cables). 200 m coil 
○ 3508BUS	Accessories  removable clamp for BUS connection - width 3.81 mm
○ 3508U2	 removable clamp 2 poles
○ 3508U3	 removable clamp 3 poles
○ 3515	 spare removable clamp

Light Now KNX



Connected controls for the Home and Building automation

SECTION 4

Light Now KNX



Connected controls for the smart home, which communicate via KNX standard bus.

How to choose devices for the composition of the electrical system

SECTION 4



SECTION 1



Type of system	Catalog section
Light Now standard system (Switches, sockets and cover plates for the residential electrical system)	1
Light Now with Netatmo (Connected controls for the smart home, which communicate via radio)	2 + 1
Light Now MyHOME (Connected controls for the smart home, which communicate via SCS BTicino bus)	3 + 1
Light Now KNX (Connected controls for the smart home, which communicate via KNX standard bus)	4 + 1

Light Now KNX

manual control units and sensors




Constantly check for presence and light levels, switching OFF as soon as the natural light level is sufficient.

Switch ON and OFF automatically

Accurate set-up on site with configuration device

Connected directly to KNX cable (supplied with tap-off connector)

The detector must be programmed using ETS software

Item	Light Now wired control units
Y4651KNX	 2 channels control unit - 4 buttons. Used to control (ON/OFF, dimming, scenario, forcing), roller shutters (up, down, stop), awnings, and other receivers. Fitted with programmable RGB LEDs (12 colors available) for displaying load status and system status feedback (normal, forced, override, day/night pilot light, etc.) and alarms. To be fitted with Light Now key cover, plate and support frame.
0 029 00	Touch screen control units With built-in temperature & proximity sensor. Max. 16 timings, 8 group events, 8 logic functions To be installed in a flush-mounting box.
0 029 01	4" touch screen - 9 control pages including switch, dimming, RGB control, shutter, scene control, HVAC control, audio control and energy metering.
0 489 19	Special sensors for corridor Ceiling mounted motion sensor Double passive infrared detection 360°, lateral range 2 x 12 m - IP 20. Recommended fixing height: 2.5 m. Fits directly in suspended ceiling with springs (supplied) or is installed in a 50 mm deep Batibox item 0 893 58. Surface mounted on ceiling using accessory item 0 488 75.
CP-MWS3A-KNX	Ceiling mounted presence sensor MW (microwave) detection, range up to 23 m Flat and compact sensor with adjustable head for special applications - IP 40. Recommended fixing height: 2.8 m. Fixes directly in suspended ceiling with springs (supplied).

Item	Special presence sensors for work areas
0 489 18	Suitable for meeting rooms, classrooms, open areas, etc. Ceiling mounted - Dual technology 360° passive infrared and ultrasound detection, range 8 m - IP 20. Fixes directly in suspended ceiling with springs (supplied) or is installed in a 50 mm deep Batibox Surface mounted on ceiling using accessory item 0 488 75. Connection by KNX red/black connector.
0 489 22	360° passive infrared detection with high density lens, range 8 m - IP 20. Fixes directly in suspended ceiling with springs (supplied) or is installed in a 50 mm deep Batibox Surface mounted on ceiling using accessory item 0 488 75. Connection by KNX red/black connector.
CP-EBDSPIR-KNX	360° passive infrared detection, range 7 m Flat and compact sensor for standard heights - IP 40. Fixes directly in suspended ceiling with springs (supplied).
CP-MWS6-KNX	360° MW (microwave) detection, range 16 m Flat and compact sensor - IP 40. Fixes directly in suspended ceiling with springs (supplied)
CP-EBDHS-KNX	Special presence sensor for high bay Ceiling mounted 360° passive infrared detection, high sensitivity, range 40 m. Flat and compact sensor for high heights- IP 65. Recommended fixing height: 15 m.
0 489 21	Special motion sensor for outdoor car parks and cellars Wall or ceiling mounted - surface mounting Passive infrared detection with 270° adjustable head, range 20 m - IP 55. Recommended fixing height: 2.5 m. Can be fixed in a corner with a special accessory item. 0 489 72.

Light Now KNX

key covers

1-FUNCTION non-silk-screen printed key covers



YD4915MH YW4915MH2 YG4915MH

Non silk-screen printed red key covers - 1 function

Color	1 module	2 modules
	Item	Item
□ White	YW4915MH	YW4915MH2
■ Stone	YG4915MH	YG4915MH2
■ Dark	YD4915MH	YD4915MH2

2-FUNCTION non-silk-screen printed key covers



YD4911MH YW4911MH2 YG4911MH

Non silk-screen printed key covers - 2 functions

Color	1 module	2 modules
	Item	Item
□ White	YW4911MH	YW4911MH2
■ Stone	YG4911MH	YG4911MH2
■ Dark	YD4911MH	YD4911MH2

1-FUNCTION silk-screen printed key covers



YG4915MHB YW4915MH2AD YD4915MHF

Silk-screen printed key covers with symbols - 1 function

Description	Color	1 module	2 modules
		Item	Item
Control of 1 dimmer	□ White	YW4915MHAD	YW4915MH2AD
	■ Stone	YG4915MHAD	YG4915MH2AD
	■ Dark	YD4915MHAD	YD4915MH2AD
Stop	□ White	YW4915MHAE	-
	■ Stone	YG4915MHAE	-
	■ Dark	YD4915MHAE	-
Staircase light	□ White	YW4915MHB	YW4915MH2B
	■ Stone	YG4915MHB	YG4915MH2B
	■ Dark	YD4915MHB	YD4915MH2B
Key	□ White	YW4915MHF	YW4915MH2F
	■ Stone	YG4915MHF	YG4915MH2F
	■ Dark	YD4915MHF	YD4915MH2F
Doorbell	□ White	YW4915MHD	YW4915MH2DM
	■ Stone	YG4915MHD	YG4915MH2DM
	■ Dark	YD4915MHD	YD4915MH2DM

2-FUNCTION silk-screen printed key covers



YD4911MHAL YG4911MHAG YW4911MH2AJ

Silk-screen printed key covers with symbols - 2 functions

Description	Color	1 module	2 modules
		Item	Item
Control of 2 dimmers	□ White	YW49112MHAD	YW49112MH2AD
	■ Stone	YG49112MHAD	YG49112MH2AD
	■ Dark	YD49112MHAD	YD49112MH2AD
On - Off	□ White	YW4911MHAG	YW4911MH2AG
	■ Stone	YG4911MHAG	YG4911MH2AG
	■ Dark	YD4911MHAG	YD4911MH2AG
Up - down	□ White	YW4911MHAH	YW4911MH2AH
	■ Stone	YG4911MHAH	YG4911MH2AH
	■ Dark	YD4911MHAH	YD4911MH2AH
On - Off plus regulation up and down	□ White	YW4911MHAI	YW4911MH2AI
	■ Stone	YG4911MHAI	YG4911MH2AI
	■ Dark	YD4911MHAI	YD4911MH2AI
Regulation + up and - down	□ White	YW4911MHAD	-
	■ Stone	YG4911MHAD	-
	■ Dark	YD4911MHAD	-
Home-away	□ White	YW4911MHAJ	YW4911MH2AJ
	■ Stone	YG4911MHAJ	YG4911MH2AJ
	■ Dark	YD4911MHAJ	YD4911MH2AJ
Day-night	□ White	YW4911MHAL	YW4911MH2AL
	■ Stone	YG4911MHAL	YG4911MH2AL
	■ Dark	YD4911MHAL	YD4911MH2AL
Scenario N° 1 - 2	□ White	YW4911MHAM	-
	■ Stone	YG4911MHAM	-
	■ Dark	YD4911MHAM	-
Scenario N° 3 - 4	□ White	YW4911MHAN	-
	■ Stone	YG4911MHAN	-
	■ Dark	YD4911MHAN	-

Dimmer	Stop	Staircase light	Key	Doorbell	On-Off	Up - down
On - Off plus regulation	Regulation + up and - down	Home-away	Day-night	Scenario N° 1 - 2	Scenario N° 3 - 4	2 Dimmer

□ White colour ■ Stone colour ■ Dark colour

Light Now KNX

modular controllers



KNX certified



0 026 65



0 026 73



0 026 79

Connected with the KNX cable
Configuration using ETS programming software

infrastructure products



KNX certified



0 026 93



0 026 92



0 035 45



0 035 07








Connected with the KNX cable
Configuration using ETS programming software

Item	Modular controllers for dimming
0 026 65	Each output can be controlled by a sensor and/or KNX control unit. For DALI control 1 output DALI bus (64 DALI ballasts max) to control up to 16 DALI groups and up to 64 DALI scenes. 4 DIN modules.
0 026 99	1 output DALI bus (64 DALI ballasts max) to control individually up to 64 DALI luminaires and up to 16 DALI scenes. 4 DIN modules.
0 026 68	For 1-10V control 10 outputs 1-10 V also controlling 10 ON/OFF circuits (16 A max). 10 DIN modules.
0 026 54	For LED and all others LV and ELV load 2 outputs 2 x 300 W/VA maximum per output. 4 DIN modules.
	Modular ON/OFF controller
0 026 80	Each output can be controlled by a sensor and/or KNX control unit. 4 x 16 A outputs. 4 DIN modules
	Modular multi-applications ON/OFF controllers
0 026 72	Each output can be controlled by a sensor and/or KNX control unit. Multi-applications controllers with independent input channels and outputs configurable to control lighting loads, power sockets, roller shutters, and HVAC equipment.
0 026 73	8 x 16 A outputs. 6 DIN modules
0 026 74	8 x 16 A outputs - 8 inputs. 6 DIN modules
0 026 76	12 x 16 A outputs - 6 DIN modules
0 026 78	16 x 16 A outputs - 10 DIN modules
0 026 79	20 x 16 A outputs - 10 DIN modules
0 026 79	20 x 16 A outputs - 18 inputs. 10 DIN modules
	Room Controller Unit
0 484 18	Power modules equipped with output contacts for controlling: - different types of ON/OFF load (lighting, roller shutters, contactors, motors, etc.) - a DALI dimming output for 64 ballasts max. Loads are managed by the controls to which they are linked: either by KNX controls, or by wired connection input terminals (switches, push-buttons, volt-free contacts). Multiphase connection and consumption measurement.
0 484 22	8 inputs - 10 outputs. 8 DIN modules 16 inputs - 16 outputs. 12 DIN modules.

Item	KNX interface - voltage contact
0 026 93	Connects voltage free contacts devices (switches, push-buttons, alarms, etc.) to the KNX.
0 026 92	Modular 4 inputs 0 to 265 AC/DC powered. 2 DIN modules.
	Flush mounting For installation in a flush-mounting box. 4 inputs - 4 outputs.
0 035 46	Line coupler Provides galvanic isolation between lines Necessary in an installation where there are more than 64 KNX participants. 2 DIN modules.
0 035 45	IP/KNX router Can act as main line or backbone coupler Links different KNX networks to each other via the IP infrastructure. 2 DIN modules.
	Modular power supplies and accessory
0 035 06	Powers one KNX line Integrated filter to prevent the short-circuit of BUS messages. Voltage 230 V \pm - 30 V= With additional 30 V unfiltered output.
0 035 07	7 DIN modules. Output 320 mA Output 640 mA
0 488 79	KNX connector Black and red. Supplied in boxes of 50
	KNX cables
0 492 91	Length 500 m 0.8 mm dia. quad Isolation 4000 V. 1 pair: red/black
0 492 92	2 pairs: red/black and yellow/white

Light Now KNX

load table at 230 V a.c. 50-60Hz

Cat.Nos	Outputs							
		Halogen lamp	ELV halogen lamp with ferromagnetic or electronic transformer	Fluorescent tube	LED and compact fluorescent lamp	Fluorescent lamp with 1-10 V ballast	DALI	Motors
Modular controllers for dimming								
0 026 65	1	-	-	-	-	-	64 ballasts (group control only)	-
0 026 99	1	-	-	-	-	-	64 ballasts (individual control)	-
0 026 68	10	-	-	-	-	4000 VA	-	-
0 026 88	4	-	-	-	-	1000 VA	-	-
0 026 54	2	2 x 300 W	2 x 200 VA	2 x 300 VA	2 x 75 W	-	-	-
Modular ON/OFF controllers								
0 026 80	4	2 x 3680 W	4 x 1000 VA	4 x [10 x (2 x 36 W)]	4 x 500 VA	-	-	4 x 500 VA
0 026 72	8	8 x 4000 VA	8 x 1800 VA	8 x 2400 VA	8 x 400 VA	-	-	8 x 1000 VA
0 026 73	8	8 x 4000 VA	8 x 1800 VA	8 x 2400 VA	8 x 400 VA	-	-	8 x 1000 VA
0 026 74	12	12 x 4000 VA	12 x 1800 VA	12 x 2400 VA	12 x 400 VA	-	-	12 x 1000 VA
0 026 76	16	16 x 4000 VA	16 x 1800 VA	16 x 2400 VA	16 x 400 VA	-	-	16 x 1000 VA
0 026 78	20	20 x 4000 VA	20 x 1800 VA	20 x 2400 VA	20 x 400 VA	-	-	20 x 1000 VA
0 026 79	20	20 x 4000 VA	20 x 1800 VA	20 x 2400 VA	20 x 400 VA	-	-	20 x 1000 VA
Room Controller Units								
0 484 18	4	4 x 500 W	4 x 250 VA	4 x [2 x (2 x 36 W)]	4 x 80 VA	-	1 x 64 ballasts	4 x 250 VA
	4	4 x 1000 W	4 x 500 VA	4 x [4 x (2 x 36 W)]	4 x 160 VA			4 x 500 VA
	2	2 x 3680 W	2 x 1000 VA	2 x [10 x (2 x 36 W)]	2 x 500 VA			2 x 500 VA
0 484 22	4	4 x 500 W	4 x 250 VA	4 x [2 x (2 x 36 W)]	4 x 80 VA	-	1 x 64 ballasts	4 x 250 VA
	8	8 x 1000 W	8 x 500 VA	8 x [4 x (2 x 36 W)]	8 x 160 VA			8 x 500 VA
	4	4 x 3680 W	4 x 1000 VA	4 x [10 x (2 x 36 W)]	4 x 500 VA			4 x 500 VA

*: Compatible with dimmable LED and compact fluorescent lamps

Light Now



Solutions for tertiary sector

Light Now

floor installation - New turrets




150700W



150710W



150725



150726

Item	New turrets
150700W	turret - white case
150710W	supporting frame 4m white
150725	horizontal junction
150726	vertical junction

Single installation



Horizontal installation

Side by side installation of two or more turrets



Utilizzare l'elemento per
giunzione orizzontale art.150725

Vertical installation

Stacking of two turrets



Utilizzare l'elemento per
giunzione verticale art.150726



150647NA



150647NB



150647NW




150640NL



150640NK


Item	Pop-up boxes
150647NA	4 modules pop-up boxes, aluminium finish
150647NW	4 modules pop-up boxes, white finish
150647NG	4 modules pop-up boxes, brass finish
150647NS	4 modules pop-up boxes, stainless steel finish
150647NB	4 modules pop-up boxes, black finish
Supporting frame and accessories	
150640NL	Metal backbox for installation in concrete floor
150640NK	Installation kit for floating floor
150647	4 modules supporting frame

Floating floor installation




Size	A* (mm)	B* (mm)
4 modules	108	131

* +/- 1 mm




Concrete floor



Light Now

floor installation - Floor boxes



Item	Floor boxes	
	Floor boxes for installation in floating and concrete floors. To be equipped with functions, RJ45 or DIN modules.	
	Modules	Cover finish
150701	8-10	customizable
150701G	8-10	grey
150702	8-10	inox
150703	16-20	customizable
150703G	16-20	grigio
150704	16-20	inox
150705	24-30	customizable
150705G	24-30	grey
150706	24-30	inox

Backboxes	
	Metal backboxes for the installation in concrete floor
	Modules
150561S	For 8-10 modules floor boxes
150563S	For 16-20 modules floor boxes
150569S	For 24-30 modules floor boxes

Supporting frames and accessories	
	To be installed in the floor boxes - in resin - (RAL 7021) anthracite colour
150721	4 modules supporting frame
150715 ⁽¹⁾	5 modules supporting frames for RJ45 110 IDC (keystone coupling)
150720	5 modules supporting frame for RJ45 110 IDC loose connectors
150716	2 modules supporting frame for DIN module (1+1)
150717	Blanking module supporting frame
150718	Internal partition for item 150721
150719 ⁽²⁾	Pre-wired module

[1] use blanking modules item C9500TB for unused compartments
[2] cannot be installed in boxes item 150705 and item 150706


Item	IP66 floor boxes
	Floor boxes for installation in floating and concrete floors. To be equipped with functions. IK 09 with the lid closed (resistance to loads 10000N).
150731	4 modules with removable lid. IP66 (when lid is closed). Can be equipped with cable exit accessory item 150734. IP54 (with cable exit accessory item 150734 and plugs inserted into the sockets). Stainless steel finish.
150732	4 modules with hinged lid. Compatible with angled plugs only. IP66 (when lid is closed). Stainless steel finish.
150733	Auto-adjustable backbox for installing IP66 floor box in concrete floors. Supplied with cover. Accepts conduits Ø16, 20, 25 mm. Minimum screed height: 65 mm
150734	Cable exit for removable lid IP66 floor box item 150731. Allows the passage of power cords when the plugs are inserted into the sockets inside the floor box. Compatible with angled plugs only. IP54 (with plugs inserted into the sockets).

The floor boxes are made in accordance with CEI 64-8 and CEI EN 60670-23 standards, and ensure the following protection index: IP4X on the perimeter of the cover and between surround plate and floor; IP2X by the cover cable outlets; IP52 near the fastening between box and floor, by means of seal. The above protection index meet the requirements for horizontal connection plugs, and for installation on raised floors for which no washing liquids are required during cleaning. The thermoplastic resins used (polycarbonate for the cover, surround plates and supports - ABS for the container) have the following resistances to abnormal heat and fire:

- UL - VO
- CEI 50-11 - IEC 60695-2-1: 850°C Glow Wire Test.


Wiring of the floor boxes is made easier by cut-outs and systems for quick cable connection. The plastic cable glands supplied as standard provide an IP4x protection index. Installation in floating floors requires the simple cutting out of a hole in one of the raised floor panels; 4 fasteners are secured to the bottom of the panel to secure the device to the hole. In concrete floors, the installation of the boxes requires the use of a metal box (item 150561S, 150563S, and 150569S), appropriately connected to the underfloor distribution system. The specific device holder support, item 150716, gives the possibility of installing in each housing DIN modular devices with capacity of up to 2 modules. The cover with reversible installation has metal hinges and a controlled spontaneous closing system, as indicated in the CEI 64-8 standard. Opening is made easier by the ergonomic handle. The cover is available in 2 stainless steel finishes, with slip prevention incisions, or with recess for customisation and integration with the floor (e.g. carpet, linoleum, etc. with thickness of 4 or 8 mm). Both types of covers have a steel reinforcement plate that ensures a load resistance of up to 3000N.

Floor boxes




Articolo	A mm	B mm	C mm	Floor hole mm
150701	185	129	210	256x170
150701G	185	129	210	256x170
150702	185	129	210	256x170
150703	305	249	210	256x290
150703G	305	249	210	256x290
150704	305	249	210	256x290
150705	441	369	210	256x410
150705G	441	369	210	256x410
150706	441	369	210	256x410

Installation box in concrete floors




Item	n° modules	A mm	B mm	C mm	D mm
150561S	8÷10	259	279	174	202
150563S	16÷20	259	279	294	322
150569S	24÷30	259	279	416	438

Installation in floating floors



Item	a (mm)	b (mm)
150701 -150701G - 150702	256	170
150703 -150703G - 150704	256	290
150705 -150705G -150706	256	410

Installation of the cover and carpet or other floor covering cutting sizes




Item	a (mm)	b (mm)
150701 - 150701G	129	210
150703 - 150703G	249	210
150705 - 150705G	369	210

Light Now


floor installation - Floor boxes

Dimensions

Floor box item 150731




Floor box item 150732




Dimensions (continued)


Flush mounting backbox item 150733




Cable exit accessory item 150734




Example of use for removable lid floor box with cable exit accessory items 150731 + 150734



Floor cut for installation in floating floor





Item Single face columns with variable height

Single face columns complete with installation accessories. Body, cover and telescopic extension, made in aluminum. Resin finishing end caps.			
	Cover	Height (mm)	Colour
129201NAL	curve	2780-4060	aluminum
129201NNR	curve	2780-4060	black
129201NBA	curve	2780-4060	white
129202NAL	flat	2780-4060	aluminum

Item Single face minicolumns with height 680 mm

Single face minicolumns complete with installation accessories. Body and cover made in aluminium. Resin finishing end caps.			
	Cover	Height (mm)	Colour
129211NAL	curve	680	aluminium
129211NNR	curve	680	black
129211NBA	curve	680	white
129212NAL	flat	680	aluminium

Item Double face columns with variable height

Double face columns complete with installation accessories. Body, cover and telescopic extension, made in aluminum. Resin finishing end caps.			
	Cover	Height (mm)	Colour
129001NNR	flat	2780-4060	aluminum
129001NAL	flat	2780-4060	black
129001NBA	flat	2780-4060	white

Item Double face minicolumns with height 680 mm

Double face minicolumns complete with installation accessories. Body and cover made in aluminium. Resin finishing end caps.			
	Cover	Height (mm)	Colour
129051NAL	flat	680	aluminum
129051NNR	flat	680	black
129051Nba	flat	680	white

Item Double face minicolumns with height 334 mm










Double face minicolumns complete with installation accessories. Body and cover made in aluminium. Resin finishing end caps.			
	Cover	Height (mm)	Colour
129101NAL	flat	334	aluminum
129101NNR	flat	334	black

Item Columns and minicolumns accesories


129085N	Linear partition, for the separation of the services inside the columns and minicolumns
120051	Installation box
120065	4 modules supporting frame
120067W	4 modules coverplate for columns and minicolumns with curved cover. White
120067G	modules coverplate for columns and minicolumns with curved cover. Grey
120067B	4 modules coverplate for columns and minicolumns with curved cover. Black

Light Now


floor installation - Columns and mini-columns

	N° modules	Installation box	Supporting frame	Coverplates
SINGLE AND DOUBLE FACE - FLAT 	4	 120051		 JA4804.. Replacing .. with letters according with desidered colours
SINGLE FACE - CURVE 	4	 120051	 120065	 120067B Black  120067G grey  120067W White

Single face columns and minicolumns



Double face columns and minicolumns



Number of cables that can be installed				
Compartment	Useful area	Number of conductors that can be installed		
		0 7 mm	0 9 mm	0 11 mm
A	6900 mm ²	120	72	50
B	6170 cm ²	106	62	44

Incara

In-desk installation



150440NW



150440NS



150442NW



150482NW



150480NW



150480NS



150443NW



150483NW

Item
150440NW
150440NS
150480NW
150480NS
150441NS

Pop-up

For flush mounting in furniture, compatible desktop thickness 15 to 40 mm Metal. Protective film
To be equipped with functions

Modules	Cover finish
4	White
4	Brushed aluminum
8	White
8	Brushed aluminum
4	Brushed aluminum (IP44)



150430NS



150430NW



150431NS



150431NW

150442NW
150443NW
150482NW
150483NW

For flush mounting in furniture, compatible desktop thickness 15 to 40 mm Metal. Protective film.
Products supplied with 2 m cord

Equipped with functions

Modules	Cover finish	Functions
4	White	n° 1 Italian std socket outlet P30 + n° 1 socket outlet P17/11 + n° 1 USB charger with 2 type A and C ports 15 W
4	White	n° 1 Italian std socket outlet P30 + n° 1 USB charger with 1 type C port 48 W PD
8	White	n° 3 Italian std socket outlet P30 + n° 1 Italian std socket outlet P17/11 + n° 1 USB charger with 2 type A and C ports 15 W
8	White	n° 2 Italian std socket outlet P30 + n° 1 Italian std socket outlet P17/11 + n° 1 USB charger with 2 type C ports 65 W PD

150430NS
150430NW
150431NS
150431NW

Top-access

For flush mounting in furniture, compatible table thickness 10 to 40 mm Metal
Easy storage for an office module, multi-outlet or surplus cable in the workspace


Dimension	Cover finish
295 mm	Metal
295 mm	White
385 mm	Metal
385 mm	White

Dimensions (mm)

Pop-up


4 modules

8 modules





Item	A	B
4 modules 150440NW - 150440NS - 150442NW - 150443NW - 150441NS	146	125
8 modules 150480NW - 150480NS - 150482NW - 150483NW	236	125

Top Access



Item	A	B	C	D
150430NS - 150430NW	130	295	120	122,2
150431NS - 150431NW	130	385	120	122,2

Incara
desktop multi-outlet




Item	Desktop multi-outlet extensions to be equipped	
	Multi-outlet extensions made of aluminium and ABS; Dimensions optimised to take up little space on the workstation. Specially designed at an angle for ease of plugging and unplugging. Can be attached with double-sided tape (provided). The double-sided tape can be removed without damaging the furniture. To be equipped with devices	
	Modules	Color
1508611W	6	White
1508611WG	6	Grey
1508612W	8	White
1508612WG	8	Grey
1508613W	12	White
1508613WG	12	Grey

Item	Desktop multi-outlet extensions equipped	
	Multi-outlet extensions made of aluminium and ABS; Dimensions optimised to take up little space on the workstation. Specially designed at an angle for ease of plugging and unplugging. Wired and equipped with a 2 m cord (H05VVF, 3G 1.5 mm2) with a 2P+E plug. Conform to standard NFC 61-314. Max. power 3680 Wat 230 VA per circuit. Can be attached with double-sided tape (provided). The double-sided tape can be removed without damaging the furniture. With power sockets and USB chargers	
	Modules	Color Description
1508661W	6	White With 2 x 2P+E sockets P30 + 1 x 15 W USB Type-A + Type-C charger
1508661WG	6	Grey With 2 x 2P+E sockets P30 + 1 x 15 W USB Type-A + Type-C charger
1508662W	8	White With 2 x 2P+E P30 sockets + 1 x 63 W USB Type-C + Type-C charger Power Delivery
	With power sockets, USB chargers and RJ45 connectors	
	Modules	Color Description
1508663W	8	White With 2 x 2P+E sockets P30 + 1 x 15 W USB Type-A + Type-C charger + 1 x RJ45
1508663WG	8	Grey With 2 x 2P+E sockets P30 + 1 x 15 W USB Type-A + Type-C charger + 1 x RJ45
	With power sockets and two-pole switch	
	Modules	Color Description
1508664W	12	White With 6 x 2P+E sockets P30 + 1 two-pole switch
1508664WG	12	Grey With 6 x 2P+E sockets P30 + 1 two-pole switch


Light Now

dimensiona data - cover plates


■ 2 modules cover plate




■ 3 modules centred cover plate




■ 3 modules cover plate




■ 4 modules supporting frame




■ 7 modules supporting frame




■ 2x2 modules cover plate wheelbase 71 - horizontal/vertical




■ 2x2x2 modules cover plate interasse 71 - horizontal/vertical




■ 2x2x2x2 modules cover plate interasse 71 - horizontal/vertical




■ 2x2 modules cover plate wheelbase 60 - horizontal/vertical




■ 2x2x2 modules cover plate wheelbase 60 - horizontal/vertical




■ 2 modules supporting frame




■ 2 modules centred supporting frame





■ 3 modules supporting frame



■ 4 modules supporting frame




■ 7 modules supporting frame




Light Now

dimensiona data - Modularity, Smarter

Smarter




XW8002 - XM8002 - XG8002



XW8002W

Modularity




1 module


2 modules

3 modules


New protruding towers





150700W



150710W



150725



150726

